

特材代碼： CVA01APHCPA7

中文品名：“埃普特”安波得親水塗層造影導管

英文品名：“APT”Angiointer Hydrophilic Angiographic Catheter

許可證字號：衛部醫器陸輸字第 001382 號

產品型號：

自 114 年 3 月 1 日生效，擴增產品型號如下：

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.10	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
11410001	4F	100	1.43	1.05	0.035	0	JR3.5	1000
11410002	4F	100	1.43	1.05	0.035	0	JR4	1000
11413003	4F	130	1.43	1.05	0.035	0	JR4	1000
11410004	4F	100	1.43	1.05	0.035	0	JR5	1000
11410005	4F	100	1.43	1.05	0.035	0	JL3.5	1000
11410006	4F	100	1.43	1.05	0.035	0	JL4	1000
11413007	4F	130	1.43	1.05	0.035	0	JL4	1000
11410008	4F	100	1.43	1.05	0.035	0	JL4.5	1000
11410009	4F	100	1.43	1.05	0.035	0	JL5	1000
11410010	4F	100	1.43	1.05	0.035	0	TIG	1000
11411011	4F	110	1.43	1.05	0.035	1/0.7	TIG	1000
11411012	4F	110	1.43	1.05	0.035	6/0.7	PIG	1000
11413013	4F	130	1.43	1.05	0.035	6/0.7	PIG	1000
11411014	4F	110	1.43	1.05	0.035	8/0.7	PIG	1000
11411015	4F	110	1.43	1.05	0.035	6/0.7	PIG-145°	1000
11413016	4F	130	1.43	1.05	0.035	6/0.7	PIG-145°	1000
11411017	4F	110	1.43	1.05	0.035	6/0.7	PIG-155°	1000
11410018	4F	100	1.43	1.05	0.035	0	MPA	1000
11410019	4F	100	1.43	1.05	0.035	2/0.7	MPA2	1000
11410020	4F	100	1.43	1.05	0.035	0	AR MOD	1000
11410021	4F	100	1.43	1.05	0.035	0	ARIMOD	1000
11410022	4F	100	1.43	1.05	0.035	0	ARIIMOD	1000
11410023	4F	100	1.43	1.05	0.035	0	ALI	1000
11410024	4F	100	1.43	1.05	0.035	0	ALII	1000
11410025	4F	100	1.43	1.05	0.035	0	ALIII	1000
11410026	4F	100	1.43	1.05	0.035	0	3DRC	1000
11408027	4F	80	1.43	1.05	0.035	0	COBRA1	1000
11408028	4F	80	1.43	1.05	0.035	0	COBRA2	1000
11408029	4F	80	1.43	1.05	0.035	0	COBRA3	1000
11410030	4F	100	1.43	1.05	0.035	0	SIM1	1000
11410031	4F	100	1.43	1.05	0.035	0	SIM2	1000
11410032	4F	100	1.43	1.05	0.035	0	SIM3	1000
11410033	4F	100	1.43	1.05	0.035	0	HEADHUNTER1	1000
11410034	4F	100	1.43	1.05	0.035	0	HEADHUNTER2	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.10	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
11410035	4F	100	1.43	1.05	0.035	0	HEADHUNTER3	1000
11410036	4F	100	1.43	1.05	0.035	0	HEADHUNTER5	1000
11410037	4F	100	1.43	1.05	0.035	0	HEADHUNTER6	1000
11408038	4F	80	1.43	1.05	0.035	0	RH	1000
11410039	4F	100	1.43	1.05	0.035	0	STRAIGHT	1000
11410040	4F	100	1.43	1.05	0.035	1/0.7	TIG	1000
11411041	4F	110	1.43	1.05	0.035	0	TIG	1000
11412542	4F	125	1.43	1.05	0.035	0	TIG	1000
11413043	4F	130	1.43	1.05	0.035	0	TIG	1000
11415044	4F	150	1.43	1.05	0.035	0	TIG	1000
11403045	4F	30	1.43	1.05	0.035	6/0.7	PIG	1000
11406046	4F	60	1.43	1.05	0.035	6/0.7	PIG	1000
11405047	4F	50	1.43	1.05	0.035	6/0.7	PIG	1000
11412548	4F	125	1.43	1.05	0.035	0	MPA	1000
11413049	4F	130	1.43	1.05	0.035	0	MPA	1000
11415050	4F	150	1.43	1.05	0.035	0	MPA	1000
11404051	4F	40	1.43	1.05	0.035	0	AR MOD	1000
11406052	4F	60	1.43	1.05	0.035	0	AR MOD	1000
11412553	4F	125	1.43	1.05	0.035	0	SIM1	1000
11413054	4F	130	1.43	1.05	0.035	0	SIM1	1000
11415055	4F	150	1.43	1.05	0.035	0	SIM1	1000
11412556	4F	125	1.43	1.05	0.035	0	SIM2	1000
11413057	4F	130	1.43	1.05	0.035	0	SIM2	1000
11415058	4F	150	1.43	1.05	0.035	0	SIM2	1000
11412559	4F	125	1.43	1.05	0.035	0	HEADHUNTER2	1000
11413060	4F	130	1.43	1.05	0.035	0	HEADHUNTER2	1000
11415061	4F	150	1.43	1.05	0.035	0	HEADHUNTER2	1000
11410062	4F	100	1.43	1.05	0.035	6/0.7	STRAIGHT	1000
11411063	4F	110	1.43	1.05	0.035	6/0.7	STRAIGHT	1000
11412564	4F	125	1.43	1.05	0.035	6/0.7	STRAIGHT	1000
11410069	4F	100	1.43	1.05	0.035	8/0.7	STRAIGHT	1000
11411070	4F	110	1.43	1.05	0.035	8/0.7	STRAIGHT	1000
11412571	4F	125	1.43	1.05	0.035	8/0.7	STRAIGHT	1000
11403072	4F	30	1.43	1.05	0.035	0	Vertebral	1000
11404073	4F	40	1.43	1.05	0.035	0	Vertebral	1000
11406574	4F	65	1.43	1.05	0.035	0	Vertebral	1000
11410075	4F	100	1.43	1.05	0.035	0	Vertebral	1000
11411076	4F	110	1.43	1.05	0.035	0	Vertebral	1000
11415077	4F	150	1.43	1.05	0.035	0	Vertebral	1000
11410078	4F	100	1.43	1.05	0.035	0	VTK	1000
11412579	4F	125	1.43	1.05	0.035	0	VTK	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.10	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
11407080	4F	70	1.43	1.05	0.035	0	Yashiro	1000
11409081	4F	90	1.43	1.05	0.035	0	RUC	1000
11406582	4F	65	1.43	1.05	0.035	0	RLG	1000
11408083	4F	80	1.43	1.05	0.035	0	RLG	1000
11410084	4F	100	1.43	1.05	0.035	0	RLG	1000
11406585	4F	65	1.43	1.05	0.035	0	MIK	1000
11408086	4F	80	1.43	1.05	0.035	0	MIK	1000
11408087	4F	80	1.43	1.05	0.035	2/0.7	COBRA1	1000
11410088	4F	100	1.43	1.05	0.035	0	COBRA1	1000
11410089	4F	100	1.43	1.05	0.035	2/0.7	COBRA1	1000
11412590	4F	125	1.43	1.05	0.035	0	COBRA1	1000
11412591	4F	125	1.43	1.05	0.035	2/0.7	COBRA1	1000
11415092	4F	150	1.43	1.05	0.035	0	COBRA1	1000
11415093	4F	150	1.43	1.05	0.035	2/0.7	COBRA1	1000
11403094	4F	30	1.43	1.05	0.035	0	COBRA2	1000
11404095	4F	40	1.43	1.05	0.035	0	COBRA2	1000
11408096	4F	80	1.43	1.05	0.035	2/0.7	COBRA2	1000
11410097	4F	100	1.43	1.05	0.035	0	COBRA2	1000
11410098	4F	100	1.43	1.05	0.035	2/0.7	COBRA2	1000
11412599	4F	125	1.43	1.05	0.035	0	COBRA2	1000
114125100	4F	125	1.43	1.05	0.035	2/0.7	COBRA2	1000
114150101	4F	150	1.43	1.05	0.035	0	COBRA2	1000
114150102	4F	150	1.43	1.05	0.035	2/0.7	COBRA2	1000
114080103	4F	80	1.43	1.05	0.035	2/0.7	COBRA3	1000
114100104	4F	100	1.43	1.05	0.035	0	COBRA3	1000
114100105	4F	100	1.43	1.05	0.035	2/0.7	COBRA3	1000
114125106	4F	125	1.43	1.05	0.035	0	COBRA3	1000
114125107	4F	125	1.43	1.05	0.035	2/0.7	COBRA3	1000
114150108	4F	150	1.43	1.05	0.035	0	COBRA3	1000
114150109	4F	150	1.43	1.05	0.035	2/0.7	COBRA3	1000
114030110	4F	30	1.43	1.05	0.035	0	RIM	1000
114040111	4F	40	1.43	1.05	0.035	0	RIM	1000
114030112	4F	30	1.43	1.05	0.035	0	Berenstein	1000
114040113	4F	40	1.43	1.05	0.035	0	Berenstein	1000
114040114	4F	40	1.43	1.05	0.035	0	KMP	1000
114060115	4F	60	1.43	1.05	0.035	0	KMP	1000
114080116	4F	80	1.43	1.05	0.035	0	KMP	1000
114100117	4F	100	1.43	1.05	0.035	0	KMP	1000
114110118	4F	110	1.43	1.05	0.035	0	KMP	1000
11510001	5F	100	1.7	1.2	0.038	0	JR3.5	1000
11510002	5F	100	1.7	1.2	0.038	0	JR4	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.10	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
11513003	5F	130	1.7	1.2	0.038	0	JR4	1000
11510004	5F	100	1.7	1.2	0.038	0	JR5	1000
11510005	5F	100	1.7	1.2	0.038	0	JL3.5	1000
11510006	5F	100	1.7	1.2	0.038	0	JL4	1000
11513007	5F	130	1.7	1.2	0.038	0	JL4	1000
11510008	5F	100	1.7	1.2	0.038	0	JL4.5	1000
11510009	5F	100	1.7	1.2	0.038	0	JL5	1000
11510010	5F	100	1.7	1.2	0.038	0	TIG	1000
11511011	5F	110	1.7	1.2	0.038	1/0.7	TIG	1000
11511012	5F	110	1.7	1.2	0.038	6/0.7	PIG	1000
11513013	5F	130	1.7	1.2	0.038	6/0.7	PIG	1000
11511014	5F	110	1.7	1.2	0.038	8/0.7	PIG	1000
11511015	5F	110	1.7	1.2	0.038	6/0.7	PIG-145°	1000
11513016	5F	130	1.7	1.2	0.038	6/0.7	PIG-145°	1000
11511017	5F	110	1.7	1.2	0.038	6/0.7	PIG-155°	1000
11511018	5F	110	1.7	1.2	0.038	8/0.7	PIG-145°	1000
11510019	5F	100	1.7	1.2	0.038	0	MPA	1000
11510020	5F	100	1.7	1.2	0.038	2/0.7	MPA2	1000
11510021	5F	100	1.7	1.2	0.038	0	AR MOD	1000
11510022	5F	100	1.7	1.2	0.038	0	ARIMOD	1000
11510023	5F	100	1.7	1.2	0.038	0	ARIIMOD	1000
11510024	5F	100	1.7	1.2	0.038	0	ALI	1000
11510025	5F	100	1.7	1.2	0.038	0	ALII	1000
11510026	5F	100	1.7	1.2	0.038	0	ALIII	1000
11510027	5F	100	1.7	1.2	0.038	0	3DRC	1000
11508028	5F	80	1.7	1.2	0.038	0	COBRA1	1000
11508029	5F	80	1.7	1.2	0.038	0	COBRA2	1000
11508030	5F	80	1.7	1.2	0.038	0	COBRA3	1000
11510031	5F	100	1.7	1.2	0.038	0	SIM1	1000
11510032	5F	100	1.7	1.2	0.038	0	SIM2	1000
11510033	5F	100	1.7	1.2	0.038	0	SIM3	1000
11510034	5F	100	1.7	1.2	0.038	0	HEADHUNTER1	1000
11510035	5F	100	1.7	1.2	0.038	0	HEADHUNTER2	1000
11510036	5F	100	1.7	1.2	0.038	0	HEADHUNTER3	1000
11510037	5F	100	1.7	1.2	0.038	0	HEADHUNTER5	1000
11510038	5F	100	1.7	1.2	0.038	0	HEADHUNTER6	1000
11508039	5F	80	1.7	1.2	0.038	0	RH	1000
11510040	5F	100	1.7	1.2	0.038	1/0.7	TIG	1000
11511041	5F	110	1.7	1.2	0.038	0	TIG	1000
11512542	5F	125	1.7	1.2	0.038	0	TIG	1000
11513043	5F	130	1.7	1.2	0.038	0	TIG	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.10	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
11515044	5F	150	1.7	1.2	0.038	0	TIG	1000
11503045	5F	30	1.7	1.2	0.038	6/0.7	PIG	1000
11506046	5F	60	1.7	1.2	0.038	6/0.7	PIG	1000
11505047	5F	50	1.7	1.2	0.038	6/0.7	PIG	1000
11512548	5F	125	1.7	1.2	0.038	0	MPA	1000
11513049	5F	130	1.7	1.2	0.038	0	MPA	1000
11515050	5F	150	1.7	1.2	0.038	0	MPA	1000
11504051	5F	40	1.7	1.2	0.038	0	AR MOD	1000
11506052	5F	60	1.7	1.2	0.038	0	AR MOD	1000
11512553	5F	125	1.7	1.2	0.038	0	SIM1	1000
11513054	5F	130	1.7	1.2	0.038	0	SIM1	1000
11515055	5F	150	1.7	1.2	0.038	0	SIM1	1000
11512556	5F	125	1.7	1.2	0.038	0	SIM2	1000
11513057	5F	130	1.7	1.2	0.038	0	SIM2	1000
11515058	5F	150	1.7	1.2	0.038	0	SIM2	1000
11512559	5F	125	1.7	1.2	0.038	0	HEADHUNTER2	1000
11513060	5F	130	1.7	1.2	0.038	0	HEADHUNTER2	1000
11515061	5F	150	1.7	1.2	0.038	0	HEADHUNTER2	1000
11503062	5F	30	1.7	1.2	0.038	0	Vertebral	1000
11504063	5F	40	1.7	1.2	0.038	0	Vertebral	1000
11506564	5F	65	1.7	1.2	0.038	0	Vertebral	1000
11510069	5F	100	1.7	1.2	0.038	0	Vertebral	1000
11509070	5F	90	1.7	1.2	0.038	0	RUC	1000
11511071	5F	110	1.7	1.2	0.038	0	Vertebral	1000
11515072	5F	150	1.7	1.2	0.038	0	Vertebral	1000
11510073	5F	100	1.7	1.2	0.038	0	VTK	1000
11512574	5F	125	1.7	1.2	0.038	0	VTK	1000
11507075	5F	70	1.7	1.2	0.038	0	Yashiro	1000
11506576	5F	65	1.7	1.2	0.038	0	RLG	1000
11508077	5F	80	1.7	1.2	0.038	0	RLG	1000
11510078	5F	100	1.7	1.2	0.038	0	RLG	1000
11506579	5F	65	1.7	1.2	0.038	0	MIK	1000
11508080	5F	80	1.7	1.2	0.038	0	MIK	1000
11508081	5F	80	1.7	1.2	0.038	2/0.7	COBRA1	1000
11510082	5F	100	1.7	1.2	0.038	0	COBRA1	1000
11510083	5F	100	1.7	1.2	0.038	2/0.7	COBRA1	1000
11512584	5F	125	1.7	1.2	0.038	0	COBRA1	1000
11512585	5F	125	1.7	1.2	0.038	2/0.7	COBRA1	1000
11515086	5F	150	1.7	1.2	0.038	0	COBRA1	1000
11515087	5F	150	1.7	1.2	0.038	2/0.7	COBRA1	1000
11503088	5F	30	1.7	1.2	0.038	2/0.7	COBRA2	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.10	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
11504089	5F	40	1.7	1.2	0.038	0	COBRA2	1000
11508090	5F	80	1.7	1.2	0.038	2/0.7	COBRA2	1000
11510091	5F	100	1.7	1.2	0.038	0	COBRA2	1000
11510092	5F	100	1.7	1.2	0.038	2/0.7	COBRA2	1000
11512593	5F	125	1.7	1.2	0.038	0	COBRA2	1000
11512594	5F	125	1.7	1.2	0.038	2/0.7	COBRA2	1000
11515095	5F	150	1.7	1.2	0.038	0	COBRA2	1000
11515096	5F	150	1.7	1.2	0.038	2/0.7	COBRA2	1000
11508097	5F	80	1.7	1.2	0.038	2/0.7	COBRA3	1000
11510098	5F	100	1.7	1.2	0.038	0	COBRA3	1000
11510099	5F	100	1.7	1.2	0.038	2/0.7	COBRA3	1000
115125100	5F	125	1.7	1.2	0.038	0	COBRA3	1000
115125101	5F	125	1.7	1.2	0.038	2/0.7	COBRA3	1000
115150102	5F	150	1.7	1.2	0.038	0	COBRA3	1000
115150103	5F	150	1.7	1.2	0.038	2/0.7	COBRA3	1000
115030104	5F	30	1.7	1.2	0.038	0	RIM	1000
115040105	5F	40	1.7	1.2	0.038	0	RIM	1000
115030106	5F	30	1.7	1.2	0.038	0	Berenstein	1000
115040107	5F	40	1.7	1.2	0.038	0	Berenstein	1000
115100108	5F	100	1.7	1.2	0.038	6/0.7	STRAIGHT	1000
115110109	5F	110	1.7	1.2	0.038	6/0.7	STRAIGHT	1000
115125110	5F	125	1.7	1.2	0.038	6/0.7	STRAIGHT	1000
115100111	5F	100	1.7	1.2	0.038	8/0.7	STRAIGHT	1000
115110112	5F	110	1.7	1.2	0.038	8/0.7	STRAIGHT	1000
115125113	5F	125	1.7	1.2	0.038	8/0.7	STRAIGHT	1000
115040114	5F	40	1.7	1.2	0.038	0	KMP	1000
115060115	5F	60	1.7	1.2	0.038	0	KMP	1000
115080116	5F	80	1.7	1.2	0.038	0	KMP	1000
115100117	5F	100	1.7	1.2	0.038	0	KMP	1000
115110118	5F	110	1.7	1.2	0.038	0	KMP	1000
11610001	6F	100	2	1.37	0.038	0	JR3.5	1000
11610002	6F	100	2	1.37	0.038	0	JR4	1000
11613003	6F	130	2	1.37	0.038	0	JR4	1000
11610004	6F	100	2	1.37	0.038	0	JR5	1000
11610005	6F	100	2	1.37	0.038	0	JL3.5	1000
11610006	6F	100	2	1.37	0.038	0	JL4	1000
11613007	6F	130	2	1.37	0.038	0	JL4	1000
11610008	6F	100	2	1.37	0.038	0	JL4.5	1000
11610009	6F	100	2	1.37	0.038	0	JL5	1000
11610010	6F	100	2	1.37	0.038	0	TIG	1000
11611011	6F	110	2	1.37	0.038	1/0.7	TIG	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.10	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
11611012	6F	110	2	1.37	0.038	6/0.7	PIG	1000
11613013	6F	130	2	1.37	0.038	6/0.7	PIG	1000
11611014	6F	110	2	1.37	0.038	8/0.7	PIG	1000
11611015	6F	110	2	1.37	0.038	6/0.7	PIG-145°	1000
11613016	6F	130	2	1.37	0.038	6/0.7	PIG-145°	1000
11611017	6F	110	2	1.37	0.038	6/0.7	PIG-155°	1000
11611018	6F	110	2	1.37	0.038	8/0.7	PIG-145°	1000
11610019	6F	100	2	1.37	0.038	0	MPA	1000
11610020	6F	100	2	1.37	0.038	2/0.7	MPA2	1000
11610021	6F	100	2	1.37	0.038	0	AR MOD	1000
11610022	6F	100	2	1.37	0.038	0	ARIMOD	1000
11610023	6F	100	2	1.37	0.038	0	ARIIMOD	1000
11610024	6F	100	2	1.37	0.038	0	ALI	1000
11610025	6F	100	2	1.37	0.038	0	ALII	1000
11610026	6F	100	2	1.37	0.038	0	ALIII	1000
11610027	6F	100	2	1.37	0.038	0	3DRC	1000
11608028	6F	80	2	1.37	0.038	0	COBRA1	1000
11608029	6F	80	2	1.37	0.038	0	COBRA2	1000
11608030	6F	80	2	1.37	0.038	0	COBRA3	1000
11610031	6F	100	2	1.37	0.038	0	SIM1	1000
11610032	6F	100	2	1.37	0.038	0	SIM2	1000
11610033	6F	100	2	1.37	0.038	0	SIM3	1000
11608034	6F	80	2	1.37	0.038	0	HEADHUNTER1	1000
11608035	6F	80	2	1.37	0.038	0	HEADHUNTER2	1000
11608036	6F	80	2	1.37	0.038	0	HEADHUNTER3	1000
11608037	6F	80	2	1.37	0.038	0	HEADHUNTER5	1000
11608038	6F	80	2	1.37	0.038	0	HEADHUNTER6	1000
11608039	6F	80	2	1.37	0.038	0	RH	1000
11610040	6F	100	2	1.37	0.038	1/0.7	TIG	1000
11611041	6F	110	2	1.37	0.038	0	TIG	1000
11606542	6F	65	2	1.37	0.038	0	Vertebral	1000
11610043	6F	100	2	1.37	0.038	0	Vertebral	1000
11611044	6F	110	2	1.37	0.038	0	Vertebral	1000
11615045	6F	150	2	1.37	0.038	0	Vertebral	1000
11610046	6F	100	2	1.37	0.038	0	VTK	1000
11612547	6F	125	2	1.37	0.038	0	VTK	1000
11607048	6F	70	2	1.37	0.038	0	Yashiro	1000
11609049	6F	90	2	1.37	0.038	0	RUC	1000
11606550	6F	65	2	1.37	0.038	0	RLG	1000
11608051	6F	80	2	1.37	0.038	0	RLG	1000
11610052	6F	100	2	1.37	0.038	0	RLG	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.10	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
11606553	6F	65	2	1.37	0.038	0	MIK	1000
11608054	6F	80	2	1.37	0.038	0	MIK	1000
11608055	6F	80	2	1.37	0.038	2/0.7	COBRA1	1000
11610056	6F	100	2	1.37	0.038	0	COBRA1	1000
11610057	6F	100	2	1.37	0.038	2/0.7	COBRA1	1000
11612558	6F	125	2	1.37	0.038	0	COBRA1	1000
11612559	6F	125	2	1.37	0.038	2/0.7	COBRA1	1000
11615060	6F	150	2	1.37	0.038	0	COBRA1	1000
11615061	6F	150	2	1.37	0.038	2/0.7	COBRA1	1000
11608062	6F	80	2	1.37	0.038	2/0.7	COBRA2	1000
11610063	6F	100	2	1.37	0.038	0	COBRA2	1000
11610064	6F	100	2	1.37	0.038	2/0.7	COBRA2	1000
11612569	6F	125	2	1.37	0.038	0	COBRA2	1000
11612570	6F	125	2	1.37	0.038	2/0.7	COBRA2	1000
11615071	6F	150	2	1.37	0.038	0	COBRA2	1000
11615072	6F	150	2	1.37	0.038	2/0.7	COBRA2	1000
11608073	6F	80	2	1.37	0.038	2/0.7	COBRA3	1000
11610074	6F	100	2	1.37	0.038	0	COBRA3	1000
11610075	6F	100	2	1.37	0.038	2/0.7	COBRA3	1000
11612576	6F	125	2	1.37	0.038	0	COBRA3	1000
11612577	6F	125	2	1.37	0.038	2/0.7	COBRA3	1000
11615078	6F	150	2	1.37	0.038	0	COBRA3	1000
11615079	6F	150	2	1.37	0.038	2/0.7	COBRA3	1000
11610080	6F	100	2	1.37	0.038	6/0.7	STRAIGHT	1000
11611081	6F	110	2	1.37	0.038	6/0.7	STRAIGHT	1000
11612582	6F	125	2	1.37	0.038	6/0.7	STRAIGHT	1000
11610083	6F	100	2	1.37	0.038	8/0.7	STRAIGHT	1000
11611084	6F	110	2	1.37	0.038	8/0.7	STRAIGHT	1000
11612585	6F	125	2	1.37	0.038	8/0.7	STRAIGHT	1000
11604086	6F	40	2	1.37	0.038	0	KMP	1000
11606087	6F	60	2	1.37	0.038	0	KMP	1000
11608088	6F	80	2	1.37	0.038	0	KMP	1000
11610089	6F	100	2	1.37	0.038	0	KMP	1000
11611090	6F	110	2	1.37	0.038	0	KMP	1000

特材代碼： CVA01APHCPA7

中文品名：“埃普特”安波得親水塗層造影導管

英文品名：“APT”Angiopointer Hydrophilic Angiographic Catheter

許可證字號：衛部醫器陸輸字第 001382 號

產品型號：

以下為 114 年 2 月 28 日以前收載之歷史資料：

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7730110001	3F	110	1.00	0.71	0.025	0	STRAIGHT	800
7730130002	3F	130	1.00	0.71	0.025	0	STRAIGHT	800
7730150003	3F	150	1.00	0.71	0.025	0	STRAIGHT	800
7730065004	3F	65	1.00	0.71	0.025	2/0.7	COBRA I	800
7730065005	3F	65	1.00	0.71	0.025	0	COBRA I	800
7730080006	3F	80	1.00	0.71	0.025	2/0.7	COBRA I	800
7730080007	3F	80	1.00	0.71	0.025	0	COBRA I	800
7730100008	3F	100	1.00	0.71	0.025	2/0.7	COBRA I	800
7730100009	3F	100	1.00	0.71	0.025	0	COBRA I	800
7730125010	3F	125	1.00	0.71	0.025	2/0.7	COBRA I	800
7730125011	3F	125	1.00	0.71	0.025	0	COBRA I	800
7730065012	3F	65	1.00	0.71	0.025	2/0.7	COBRA II	800
7730065013	3F	65	1.00	0.71	0.025	0	COBRA II	800
7730080014	3F	80	1.00	0.71	0.025	2/0.7	COBRA II	800
7730080015	3F	80	1.00	0.71	0.025	0	COBRA II	800
7730100216	3F	100	1.00	0.71	0.025	2/0.7	COBRA II	800
7730100217	3F	100	1.00	0.71	0.025	0	COBRA II	800
7730125218	3F	125	1.00	0.71	0.025	2/0.7	COBRA II	800
7730125219	3F	125	1.00	0.71	0.025	0	COBRA II	800
7730065220	3F	65	1.00	0.71	0.025	2/0.7	COBRA III	800
7730065221	3F	65	1.00	0.71	0.025	0	COBRA III	800
7730080222	3F	80	1.00	0.71	0.025	2/0.7	COBRA III	800
7730080223	3F	80	1.00	0.71	0.025	0	COBRA III	800
7730100224	3F	100	1.00	0.71	0.025	2/0.7	COBRA III	800
7730100225	3F	100	1.00	0.71	0.025	0	COBRA III	800
7730125226	3F	125	1.00	0.71	0.025	2/0.7	COBRA III	800
7730125227	3F	125	1.00	0.71	0.025	0	COBRA III	800
7733040001	3.3F	40	1.18	0.81	0.030	6/0.7	STRAIGHT	1000
7733040002	3.3F	40	1.18	0.81	0.030	0	STRAIGHT	1000
7733060003	3.3F	60	1.18	0.81	0.030	6/0.7	STRAIGHT	1000
7733060004	3.3F	60	1.18	0.81	0.030	0	STRAIGHT	1000
7733080005	3.3F	80	1.18	0.81	0.030	6/0.7	STRAIGHT	1000
7733080006	3.3F	80	1.18	0.81	0.030	0	STRAIGHT	1000
7733100007	3.3F	100	1.18	0.81	0.030	6/0.7	STRAIGHT	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7733100008	3.3F	100	1.18	0.81	0.030	0	STRAIGHT	1000
7733130009	3.3F	130	1.18	0.81	0.030	6/0.7	STRAIGHT	1000
7733130010	3.3F	130	1.18	0.81	0.030	0	STRAIGHT	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7733150011	3.3F	150	1.18	0.81	0.030	6/0.7	STRAIGHT	1000
7733150012	3.3F	150	1.18	0.81	0.030	0	STRAIGHT	1000
7733040013	3.3F	40	1.18	0.81	0.030	6/0.7	PIG	1000
7733060014	3.3F	60	1.18	0.81	0.030	6/0.7	PIG	1000
7733080015	3.3F	80	1.18	0.81	0.030	6/0.7	PIG	1000
7733100016	3.3F	100	1.18	0.81	0.030	6/0.7	PIG	1000
7733130017	3.3F	130	1.18	0.81	0.030	6/0.7	PIG	1000
7733040018	3.3F	40	1.18	0.81	0.030	8/0.7	PIG	1000
7733060019	3.3F	60	1.18	0.81	0.030	8/0.7	PIG	1000
7733080020	3.3F	80	1.18	0.81	0.030	8/0.7	PIG	1000
7733100021	3.3F	100	1.18	0.81	0.030	8/0.7	PIG	1000
7733130022	3.3F	130	1.18	0.81	0.030	8/0.7	PIG	1000
7733040023	3.3F	40	1.18	0.81	0.030	6/0.7	PIG-145°	1000
7733060024	3.3F	60	1.18	0.81	0.030	6/0.7	PIG-145°	1000
7733080025	3.3F	80	1.18	0.81	0.030	6/0.7	PIG-145°	1000
7733100026	3.3F	100	1.18	0.81	0.030	6/0.7	PIG-145°	1000
7733130027	3.3F	130	1.18	0.81	0.030	6/0.7	PIG-145°	1000
7733040028	3.3F	40	1.18	0.81	0.030	8/0.7	PIG-145°	1000
7733060029	3.3F	60	1.18	0.81	0.030	8/0.7	PIG-145°	1000
7733080030	3.3F	80	1.18	0.81	0.030	8/0.7	PIG-145°	1000
7733100031	3.3F	100	1.18	0.81	0.030	8/0.7	PIG-145°	1000
7733130032	3.3F	130	1.18	0.81	0.030	8/0.7	PIG-145°	1000
7733040033	3.3F	40	1.18	0.81	0.030	6/0.7	PIG-155°	1000
7733060034	3.3F	60	1.18	0.81	0.030	6/0.7	PIG-155°	1000
7733080035	3.3F	80	1.18	0.81	0.030	6/0.7	PIG-155°	1000
7733100036	3.3F	100	1.18	0.81	0.030	6/0.7	PIG-155°	1000
7733130037	3.3F	130	1.18	0.81	0.030	6/0.7	PIG-155°	1000
7733040038	3.3F	40	1.18	0.81	0.030	8/0.7	PIG-155°	1000
7733060039	3.3F	60	1.18	0.81	0.030	8/0.7	PIG-155°	1000
7733080040	3.3F	80	1.18	0.81	0.030	8/0.7	PIG-155°	1000
7733100041	3.3F	100	1.18	0.81	0.030	8/0.7	PIG-155°	1000
7733130042	3.3F	130	1.18	0.81	0.030	8/0.7	PIG-155°	1000
7733040043	3.3F	40	1.18	0.81	0.030	0	Vertebral	1000
7733060044	3.3F	60	1.18	0.81	0.030	0	Vertebral	1000
7733080045	3.3F	80	1.18	0.81	0.030	0	Vertebral	1000
7733065046	3.3F	65	1.18	0.81	0.030	2/0.7	MPA	1000
7733040047	3.3F	40	1.18	0.81	0.030	0	MPA	1000
7733060048	3.3F	60	1.18	0.81	0.030	2/0.7	MPA	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7733060049	3.3F	60	1.18	0.81	0.030	0	MPA	1000
7733080050	3.3F	80	1.18	0.81	0.030	2/0.7	MPA	1000
7733080051	3.3F	80	1.18	0.81	0.030	0	MPA	1000
7733100052	3.3F	100	1.18	0.81	0.030	2/0.7	MPA	1000
7733100053	3.3F	100	1.18	0.81	0.030	0	MPA	1000
7733040054	3.3F	40	1.18	0.81	0.030	2/0.7	MPB	1000
7733040055	3.3F	40	1.18	0.81	0.030	0	MPB	1000
7733080056	3.3F	80	1.18	0.81	0.030	2/0.7	MPB	1000
7733080057	3.3F	80	1.18	0.81	0.030	0	MPB	1000
7733100058	3.3F	100	1.18	0.81	0.030	2/0.7	MPB	1000
7733100059	3.3F	100	1.18	0.81	0.030	0	MPB	1000
7733125060	3.3F	125	1.18	0.81	0.030	2/0.7	MPB	1000
7733125061	3.3F	125	1.18	0.81	0.030	0	MPB	1000
7733040062	3.3F	40	1.18	0.81	0.030	2/0.7	MPC	1000
7733040063	3.3F	40	1.18	0.81	0.030	0	MPC	1000
7733060064	3.3F	60	1.18	0.81	0.030	2/0.7	MPC	1000
7733060065	3.3F	60	1.18	0.81	0.030	0	MPC	1000
7733080066	3.3F	80	1.18	0.81	0.030	2/0.7	MPC	1000
7733080067	3.3F	80	1.18	0.81	0.030	0	MPC	1000
7733100068	3.3F	100	1.18	0.81	0.030	2/0.7	MPC	1000
7733100069	3.3F	100	1.18	0.81	0.030	0	MPC	1000
7733040070	3.3F	40	1.18	0.81	0.030	2/0.7	MPD	1000
7733040071	3.3F	40	1.18	0.81	0.030	0	MPD	1000
7733060072	3.3F	60	1.18	0.81	0.030	2/0.7	MPD	1000
7733060073	3.3F	60	1.18	0.81	0.030	0	MPD	1000
7733080074	3.3F	80	1.18	0.81	0.030	2/0.7	MPD	1000
7733080075	3.3F	80	1.18	0.81	0.030	0	MPD	1000
7733100076	3.3F	100	1.18	0.81	0.030	2/0.7	MPD	1000
7733100077	3.3F	100	1.18	0.81	0.030	0	MPD	1000
7733040078	3.3F	40	1.18	0.81	0.030	2/0.7	MPE	1000
7733040079	3.3F	40	1.18	0.81	0.030	0	MPE	1000
7733060080	3.3F	60	1.18	0.81	0.030	2/0.7	MPE	1000
7733060081	3.3F	60	1.18	0.81	0.030	0	MPE	1000
7733080082	3.3F	80	1.18	0.81	0.030	2/0.7	MPE	1000
7733080083	3.3F	80	1.18	0.81	0.030	0	MPE	1000
7733100084	3.3F	100	1.18	0.81	0.030	2/0.7	MPE	1000
7733080085	3.3F	80	1.18	0.81	0.030	0	Mani	1000
7733080086	3.3F	80	1.18	0.81	0.030	0	Bentson I	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7733080087	3.3F	80	1.18	0.81	0.030	0	Bentson II	1000
7733080088	3.3F	80	1.18	0.81	0.030	0	Bentson III	1000
7733080089	3.3F	80	1.18	0.81	0.030	2/0.7	SIM I	1000
7733080090	3.3F	80	1.18	0.81	0.030	0	SIM I	1000
7733080091	3.3F	80	1.18	0.81	0.030	2/0.7	SIM II	1000
7733080092	3.3F	80	1.18	0.81	0.030	0	SIM II	1000
7733080093	3.3F	80	1.18	0.81	0.030	2/0.7	SIM III	1000
7733080094	3.3F	80	1.18	0.81	0.030	0	SIM III	1000
7733040095	3.3F	40	1.18	0.81	0.030	2/0.7	COBRA I	1000
7733040096	3.3F	40	1.18	0.81	0.030	0	COBRA I	1000
7733060097	3.3F	60	1.18	0.81	0.030	2/0.7	COBRA I	1000
7733060098	3.3F	60	1.18	0.81	0.030	0	COBRA I	1000
7733080099	3.3F	80	1.18	0.81	0.030	2/0.7	COBRA I	1000
7733080100	3.3F	80	1.18	0.81	0.030	0	COBRA I	1000
7733100101	3.3F	100	1.18	0.81	0.030	2/0.7	COBRA I	1000
7733100102	3.3F	100	1.18	0.81	0.030	0	COBRA I	1000
7733040103	3.3F	40	1.18	0.81	0.030	2/0.7	COBRA II	1000
7733040104	3.3F	40	1.18	0.81	0.030	0	COBRA II	1000
7733060105	3.3F	60	1.18	0.81	0.030	2/0.7	COBRA II	1000
7733060106	3.3F	60	1.18	0.81	0.030	0	COBRA II	1000
7733080107	3.3F	80	1.18	0.81	0.030	2/0.7	COBRA II	1000
7733080108	3.3F	80	1.18	0.81	0.030	0	COBRA II	1000
7733100109	3.3F	100	1.18	0.81	0.030	2/0.7	COBRA II	1000
7733100110	3.3F	100	1.18	0.81	0.030	0	COBRA II	1000
7733040111	3.3F	40	1.18	0.81	0.030	2/0.7	COBRA III	1000
7733040112	3.3F	40	1.18	0.81	0.030	0	COBRA III	1000
7733060113	3.3F	60	1.18	0.81	0.030	2/0.7	COBRA III	1000
7733060114	3.3F	60	1.18	0.81	0.030	0	COBRA III	1000
7733080115	3.3F	80	1.18	0.81	0.030	2/0.7	COBRA III	1000
7733080116	3.3F	80	1.18	0.81	0.030	0	COBRA III	1000
7733100117	3.3F	100	1.18	0.81	0.030	2/0.7	COBRA III	1000
7733100118	3.3F	100	1.18	0.81	0.030	0	COBRA III	1000
7733040119	3.3F	40	1.18	0.81	0.030	2/0.7	Renal small	1000
7733060120	3.3F	60	1.18	0.81	0.030	0	Renal small	1000
7733080121	3.3F	80	1.18	0.81	0.030	0	Renal small	1000
7733100122	3.3F	110	1.18	0.81	0.030	0	Renal small	1000
7733130123	3.3F	130	1.18	0.81	0.030	2/0.7	Renal small	1000
7733150124	3.3F	150	1.18	0.81	0.030	0	Renal small	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7733060125	3.3F	60	1.18	0.81	0.030	2/0.7	Renal Double	1000
7733060126	3.3F	60	1.18	0.81	0.030	0	Renal Double	1000
7733040127	3.3F	40	1.18	0.81	0.030	2/0.7	Renal Double	1000
7733040128	3.3F	40	1.18	0.81	0.030	0	Renal Double	1000
7733040129	3.3F	40	1.18	0.81	0.030	0	Shepherd Hook I	1000
7733040130	3.3F	40	1.18	0.81	0.030	0	Shepherd Hook II	1000
7733040131	3.3F	40	1.18	0.81	0.030	0	J-Curve I	1000
7733040132	3.3F	40	1.18	0.81	0.030	0	J-Curve II	1000
7733040133	3.3F	40	1.18	0.81	0.030	0	J-Curve III	1000
7733080134	3.3F	80	1.18	0.81	0.030	0	HeadHunter 1	1000
7733100135	3.3F	100	1.18	0.81	0.030	0	HeadHunter 2	1000
7733080136	3.3F	80	1.18	0.81	0.030	0	HeadHunter 2	1000
7733080137	3.3F	80	1.18	0.81	0.030	0	HeadHunter 3	1000
7733080138	3.3F	80	1.18	0.81	0.030	0	HeadHunter 5	1000
7733080139	3.3F	80	1.18	0.81	0.030	0	HeadHunter 6	1000
7733080140	3.3F	80	1.18	0.81	0.030	0	VTK	1000
7733100141	3.3F	100	1.18	0.81	0.030	0	VTK	1000
7733060142	3.3F	60	1.18	0.81	0.030	0	VS	1000
7733060143	3.3F	60	1.18	0.81	0.030	0	VS 1	1000
7733080144	3.3F	80	1.18	0.81	0.030	0	VS 1	1000
7733060145	3.3F	60	1.18	0.81	0.030	0	VS 2	1000
7733060146	3.3F	60	1.18	0.81	0.030	0	VS 3	1000
7733070147	3.3F	70	1.18	0.81	0.030	0	RUC	1000
7733060148	3.3F	60	1.18	0.81	0.030	0	Yashiro	1000
7733060149	3.3F	60	1.18	0.81	0.030	0	RH	1000
7733080150	3.3F	80	1.18	0.81	0.030	0	IM	1000
7733040151	3.3F	40	1.18	0.81	0.030	0	RLG	1000
7733080152	3.3F	80	1.18	0.81	0.030	0	RLG	1000
7733080153	3.3F	80	1.18	0.81	0.030	0	RS	1000
7733080154	3.3F	80	1.18	0.81	0.030	0	JL3.5	1000
7733110155	3.3F	110	1.18	0.81	0.030	0	JL3.5	1000
7733130156	3.3F	130	1.18	0.81	0.030	0	JL3.5	1000
7733080157	3.3F	80	1.18	0.81	0.030	0	JL4	1000
7733110158	3.3F	110	1.18	0.81	0.030	0	JL4	1000
7733130159	3.3F	130	1.18	0.81	0.030	0	JL4	1000
7733080160	3.3F	80	1.18	0.81	0.030	0	JL4.5	1000
7733110161	3.3F	110	1.18	0.81	0.030	0	JL4.5	1000
7733130162	3.3F	130	1.18	0.81	0.030	0	JL4.5	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7733080163	3.3F	80	1.18	0.81	0.030	0	JL5	1000
7733110164	3.3F	110	1.18	0.81	0.030	0	JL5	1000
7733130165	3.3F	130	1.18	0.81	0.030	0	JL5	1000
7733080166	3.3F	80	1.18	0.81	0.030	0	JL6	1000
7733110167	3.3F	110	1.18	0.81	0.030	0	JL6	1000
7733130168	3.3F	130	1.18	0.81	0.030	0	JL6	1000
7733080169	3.3F	80	1.18	0.81	0.030	0	JR3.5	1000
7733110170	3.3F	110	1.18	0.81	0.030	0	JR3.5	1000
7733130171	3.3F	130	1.18	0.81	0.030	0	JR3.5	1000
7733080172	3.3F	80	1.18	0.81	0.030	0	JR4	1000
7733110173	3.3F	110	1.18	0.81	0.030	0	JR4	1000
7733130174	3.3F	130	1.18	0.81	0.030	0	JR4	1000
7733080175	3.3F	80	1.18	0.81	0.030	0	JR5	1000
7733110176	3.3F	110	1.18	0.81	0.030	0	JR5	1000
7733130177	3.3F	130	1.18	0.81	0.030	0	JR5	1000
7733080178	3.3F	80	1.18	0.81	0.030	0	JR6	1000
7733110179	3.3F	110	1.18	0.81	0.030	0	JR6	1000
7733130180	3.3F	130	1.18	0.81	0.030	0	JR6	1000
7733040181	3.3F	40	1.18	0.81	0.030	5/0.7	UNIV	1000
7733040182	3.3F	40	1.18	0.81	0.030	8/0.7	UNIV	1000
7733070183	3.3F	70	1.18	0.81	0.030	5/0.7	UNIV	1000
7733070184	3.3F	70	1.18	0.81	0.030	8/0.7	UNIV	1000
7733110185	3.3F	110	1.18	0.81	0.030	5/0.7	UNIV	1000
7733110186	3.3F	110	1.18	0.81	0.030	8/0.7	UNIV	1000
7733060187	3.3F	60	1.18	0.81	0.030	0	TRG	1000
7733060188	3.3F	60	1.18	0.81	0.030	1/0.7	TRG	1000
7733080189	3.3F	80	1.18	0.81	0.030	0	TRG	1000
7733080190	3.3F	80	1.18	0.81	0.030	1/0.7	TRG	1000
7733110191	3.3F	110	1.18	0.81	0.030	0	TRG	1000
7733110192	3.3F	110	1.18	0.81	0.030	1/0.7	TRG	1000
7733060193	3.3F	60	1.18	0.81	0.030	0	TRG 1	1000
7733060194	3.3F	60	1.18	0.81	0.030	2/0.7	TRG 1	1000
7733080195	3.3F	80	1.18	0.81	0.030	0	TRG 1	1000
7733080196	3.3F	80	1.18	0.81	0.030	2/0.7	TRG 1	1000
7733110197	3.3F	110	1.18	0.81	0.030	0	TRG 1	1000
7733110198	3.3F	110	1.18	0.81	0.030	2/0.7	TRG 1	1000
7733060199	3.3F	60	1.18	0.81	0.030	0	TRG 2	1000
7733060200	3.3F	60	1.18	0.81	0.030	1/0.7	TRG 2	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7733080201	3.3F	80	1.18	0.81	0.030	0	TRG 2	1000
7733080202	3.3F	80	1.18	0.81	0.030	1/0.7	TRG 2	1000
7733110203	3.3F	110	1.18	0.81	0.030	0	TRG 2	1000
7733110204	3.3F	110	1.18	0.81	0.030	1/0.7	TRG 2	1000
7740065001	4F	65	1.42	1.02	0.035	6/0.7	STRAIGHT	1000
7740065002	4F	65	1.42	1.02	0.035	0	STRAIGHT	1000
7740080003	4F	80	1.42	1.02	0.035	6/0.7	STRAIGHT	1000
7740080004	4F	80	1.42	1.02	0.035	0	STRAIGHT	1000
7740100005	4F	100	1.42	1.02	0.035	6/0.7	STRAIGHT	1000
7740100006	4F	100	1.42	1.02	0.035	0	STRAIGHT	1000
7740110007	4F	110	1.42	1.02	0.035	6/0.7	STRAIGHT	1000
7740110008	4F	110	1.42	1.02	0.035	0	STRAIGHT	1000
7740120009	4F	120	1.42	1.02	0.035	6/0.7	STRAIGHT	1000
7740120010	4F	120	1.42	1.02	0.035	0	STRAIGHT	1000
7740150011	4F	150	1.42	1.02	0.035	6/0.7	STRAIGHT	1000
7740150012	4F	150	1.42	1.02	0.035	0	STRAIGHT	1000
7740065013	4F	65	1.42	1.02	0.035	6/0.7	PIG	1000
7740080014	4F	80	1.42	1.02	0.035	6/0.7	PIG	1000
7740100015	4F	100	1.42	1.02	0.035	6/0.7	PIG	1000
7740110016	4F	110	1.42	1.02	0.035	6/0.7	PIG	1000
7740130017	4F	130	1.42	1.02	0.035	6/0.7	PIG	1000
7740065018	4F	65	1.42	1.02	0.035	8/0.7	PIG	1000
7740080019	4F	80	1.42	1.02	0.035	8/0.7	PIG	1000
7740100020	4F	100	1.42	1.02	0.035	8/0.7	PIG	1000
7740110021	4F	110	1.42	1.02	0.035	8/0.7	PIG	1000
7740130022	4F	130	1.42	1.02	0.035	8/0.7	PIG	1000
7740065023	4F	65	1.42	1.02	0.035	6/0.7	PIG-145°	1000
7740080024	4F	80	1.42	1.02	0.035	6/0.7	PIG-145°	1000
7740100025	4F	100	1.42	1.02	0.035	6/0.7	PIG-145°	1000
7740110026	4F	110	1.42	1.02	0.035	6/0.7	PIG-145°	1000
7740130027	4F	130	1.42	1.02	0.035	6/0.7	PIG-145°	1000
7740065028	4F	65	1.42	1.02	0.035	8/0.7	PIG-145°	1000
7740080029	4F	80	1.42	1.02	0.035	8/0.7	PIG-145°	1000
7740100030	4F	100	1.42	1.02	0.035	8/0.7	PIG-145°	1000
7740110031	4F	110	1.42	1.02	0.035	8/0.7	PIG-145°	1000
7740130032	4F	130	1.42	1.02	0.035	8/0.7	PIG-145°	1000
7740065033	4F	65	1.42	1.02	0.035	6/0.7	PIG-155°	1000
7740080034	4F	80	1.42	1.02	0.035	6/0.7	PIG-155°	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7740100035	4F	100	1.42	1.02	0.035	6/0.7	PIG-155°	1000
7740110036	4F	110	1.42	1.02	0.035	6/0.7	PIG-155°	1000
7740130037	4F	130	1.42	1.02	0.035	6/0.7	PIG-155°	1000
7740065038	4F	65	1.42	1.02	0.035	8/0.7	PIG-155°	1000
7740080039	4F	80	1.42	1.02	0.035	8/0.7	PIG-155°	1000
7740100040	4F	100	1.42	1.02	0.035	8/0.7	PIG-155°	1000
7740110041	4F	110	1.42	1.02	0.035	8/0.7	PIG-155°	1000
7740130042	4F	130	1.42	1.02	0.035	8/0.7	PIG-155°	1000
7740065043	4F	65	1.42	1.02	0.035	0	Vertebral	1000
7740100044	4F	100	1.42	1.02	0.035	0	Vertebral	1000
7740110045	4F	110	1.42	1.02	0.035	0	Vertebral	1000
7740065046	4F	65	1.42	1.02	0.035	2/0.7	MPA	1000
7740065047	4F	65	1.42	1.02	0.035	0	MPA	1000
7740080048	4F	80	1.42	1.02	0.035	2/0.7	MPA	1000
7740080049	4F	80	1.42	1.02	0.035	0	MPA	1000
7740100050	4F	100	1.42	1.02	0.035	2/0.7	MPA	1000
7740100051	4F	100	1.42	1.02	0.035	0	MPA	1000
7740125052	4F	125	1.42	1.02	0.035	2/0.7	MPA	1000
7740125053	4F	125	1.42	1.02	0.035	0	MPA	1000
7740065054	4F	65	1.42	1.02	0.035	2/0.7	MPB	1000
7740065055	4F	65	1.42	1.02	0.035	0	MPB	1000
7740080056	4F	80	1.42	1.02	0.035	2/0.7	MPB	1000
7740080057	4F	80	1.42	1.02	0.035	0	MPB	1000
7740100058	4F	100	1.42	1.02	0.035	2/0.7	MPB	1000
7740100059	4F	100	1.42	1.02	0.035	0	MPB	1000
7740125060	4F	125	1.42	1.02	0.035	2/0.7	MPB	1000
7740125061	4F	125	1.42	1.02	0.035	0	MPB	1000
7740065062	4F	65	1.42	1.02	0.035	2/0.7	MPC	1000
7740065063	4F	65	1.42	1.02	0.035	0	MPC	1000
7740080064	4F	80	1.42	1.02	0.035	2/0.7	MPC	1000
7740080065	4F	80	1.42	1.02	0.035	0	MPC	1000
7740100066	4F	100	1.42	1.02	0.035	2/0.7	MPC	1000
7740100067	4F	100	1.42	1.02	0.035	0	MPC	1000
7740125068	4F	125	1.42	1.02	0.035	2/0.7	MPC	1000
7740125069	4F	125	1.42	1.02	0.035	0	MPC	1000
7740065070	4F	65	1.42	1.02	0.035	2/0.7	MPD	1000
7740065071	4F	65	1.42	1.02	0.035	0	MPD	1000
7740080072	4F	80	1.42	1.02	0.035	2/0.7	MPD	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7740080073	4F	80	1.42	1.02	0.035	0	MPD	1000
7740100074	4F	100	1.42	1.02	0.035	2/0.7	MPD	1000
7740100075	4F	100	1.42	1.02	0.035	0	MPD	1000
7740125076	4F	125	1.42	1.02	0.035	2/0.7	MPD	1000
7740125077	4F	125	1.42	1.02	0.035	0	MPD	1000
7740065078	4F	65	1.42	1.02	0.035	2/0.7	MPE	1000
7740065079	4F	65	1.42	1.02	0.035	0	MPE	1000
7740080080	4F	80	1.42	1.02	0.035	2/0.7	MPE	1000
7740080081	4F	80	1.42	1.02	0.035	0	MPE	1000
7740100082	4F	100	1.42	1.02	0.035	2/0.7	MPE	1000
7740100083	4F	100	1.42	1.02	0.035	0	MPE	1000
7740125084	4F	125	1.42	1.02	0.035	2/0.7	MPE	1000
7740100085	4F	100	1.42	1.02	0.035	0	Mani	1000
7740100086	4F	100	1.42	1.02	0.035	0	Bentson I	1000
7740100087	4F	100	1.42	1.02	0.035	0	Bentson II	1000
7740100088	4F	100	1.42	1.02	0.035	0	Bentson III	1000
7740100089	4F	100	1.42	1.02	0.035	2/0.7	SIM I	1000
7740100090	4F	100	1.42	1.02	0.035	0	SIM I	1000
7740100091	4F	100	1.42	1.02	0.035	2/0.7	SIM II	1000
7740100092	4F	100	1.42	1.02	0.035	0	SIM II	1000
7740100093	4F	100	1.42	1.02	0.035	2/0.7	SIM III	1000
7740100094	4F	100	1.42	1.02	0.035	0	SIM III	1000
7740065095	4F	65	1.42	1.02	0.035	2/0.7	COBRA I	1000
7740065096	4F	65	1.42	1.02	0.035	0	COBRA I	1000
7740080097	4F	80	1.42	1.02	0.035	2/0.7	COBRA I	1000
7740080098	4F	80	1.42	1.02	0.035	0	COBRA I	1000
7740100099	4F	100	1.42	1.02	0.035	2/0.7	COBRA I	1000
7740100100	4F	100	1.42	1.02	0.035	0	COBRA I	1000
7740125101	4F	125	1.42	1.02	0.035	2/0.7	COBRA I	1000
7740125102	4F	125	1.42	1.02	0.035	0	COBRA I	1000
7740065103	4F	65	1.42	1.02	0.035	2/0.7	COBRA II	1000
7740065104	4F	65	1.42	1.02	0.035	0	COBRA II	1000
7740080105	4F	80	1.42	1.02	0.035	2/0.7	COBRA II	1000
7740080106	4F	80	1.42	1.02	0.035	0	COBRA II	1000
7740100107	4F	100	1.42	1.02	0.035	2/0.7	COBRA II	1000
7740100108	4F	100	1.42	1.02	0.035	0	COBRA II	1000
7740125109	4F	125	1.42	1.02	0.035	2/0.7	COBRA II	1000
7740125110	4F	125	1.42	1.02	0.035	0	COBRA II	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7740065111	4F	65	1.42	1.02	0.035	2/0.7	COBRA III	1000
7740065112	4F	65	1.42	1.02	0.035	0	COBRA III	1000
7740080113	4F	80	1.42	1.02	0.035	2/0.7	COBRA III	1000
7740080114	4F	80	1.42	1.02	0.035	0	COBRA III	1000
7740100115	4F	100	1.42	1.02	0.035	2/0.7	COBRA III	1000
7740100116	4F	100	1.42	1.02	0.035	0	COBRA III	1000
7740125117	4F	125	1.42	1.02	0.035	2/0.7	COBRA III	1000
7740125118	4F	125	1.42	1.02	0.035	0	COBRA III	1000
7740065119	4F	65	1.42	1.02	0.035	2/0.7	Renal small	1000
7740080120	4F	80	1.42	1.02	0.035	0	Renal small	1000
7740100121	4F	100	1.42	1.02	0.035	0	Renal small	1000
7740130122	4F	130	1.42	1.02	0.035	0	Renal small	1000
7740150123	4F	150	1.42	1.02	0.035	2/0.7	Renal small	1000
7740150124	4F	150	1.42	1.02	0.035	0	Renal small	1000
7740080125	4F	80	1.42	1.02	0.035	2/0.7	Renal Double	1000
7740080126	4F	80	1.42	1.02	0.035	0	Renal Double	1000
7740065127	4F	65	1.42	1.02	0.035	2/0.7	Renal Double	1000
7740065128	4F	65	1.42	1.02	0.035	0	Renal Double	1000
7740065129	4F	65	1.42	1.02	0.035	0	Shepherd Hook I	1000
7740065130	4F	65	1.42	1.02	0.035	0	Shepherd Hook II	1000
7740065131	4F	65	1.42	1.02	0.035	0	J-Curve I	1000
7740065132	4F	65	1.42	1.02	0.035	0	J-Curve II	1000
7740065133	4F	65	1.42	1.02	0.035	0	J-Curve III	1000
7740100134	4F	100	1.42	1.02	0.035	0	HeadHunter 1	1000
7740125135	4F	125	1.42	1.02	0.035	0	HeadHunter 2	1000
7740100136	4F	100	1.42	1.02	0.035	0	HeadHunter 2	1000
7740100137	4F	100	1.42	1.02	0.035	0	HeadHunter 3	1000
7740100138	4F	100	1.42	1.02	0.035	0	HeadHunter 5	1000
7740100139	4F	100	1.42	1.02	0.035	0	HeadHunter 6	1000
7740100140	4F	100	1.42	1.02	0.035	0	VTK	1000
7740125141	4F	125	1.42	1.02	0.035	0	VTK	1000
7740080142	4F	80	1.42	1.02	0.035	0	VS	1000
7740080143	4F	80	1.42	1.02	0.035	0	VS 1	1000
7740125144	4F	125	1.42	1.02	0.035	0	VS 1	1000
7740080145	4F	80	1.42	1.02	0.035	0	VS 2	1000
7740080146	4F	80	1.42	1.02	0.035	0	VS 3	1000
7740090147	4F	90	1.42	1.02	0.035	0	RUC	1000
7740070148	4F	70	1.42	1.02	0.035	0	Yashiro	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7740080149	4F	80	1.42	1.02	0.035	0	RH	1000
7740100150	4F	100	1.42	1.02	0.035	0	IM	1000
7740065151	4F	65	1.42	1.02	0.035	0	RLG	1000
7740100152	4F	100	1.42	1.02	0.035	0	RLG	1000
7740080153	4F	80	1.42	1.02	0.035	0	RS	1000
7740100154	4F	100	1.42	1.02	0.035	0	JL3.5	1000
7740110155	4F	110	1.42	1.02	0.035	0	JL3.5	1000
7740130156	4F	130	1.42	1.02	0.035	0	JL3.5	1000
7740100157	4F	100	1.42	1.02	0.035	0	JL4	1000
7740110158	4F	110	1.42	1.02	0.035	0	JL4	1000
7740130159	4F	130	1.42	1.02	0.035	0	JL4	1000
7740100160	4F	100	1.42	1.02	0.035	0	JL4.5	1000
7740110161	4F	110	1.42	1.02	0.035	0	JL4.5	1000
7740130162	4F	130	1.42	1.02	0.035	0	JL4.5	1000
7740100163	4F	100	1.42	1.02	0.035	0	JL5	1000
7740110164	4F	110	1.42	1.02	0.035	0	JL5	1000
7740130165	4F	130	1.42	1.02	0.035	0	JL5	1000
7740100166	4F	100	1.42	1.02	0.035	0	JL6	1000
7740110167	4F	110	1.42	1.02	0.035	0	JL6	1000
7740130168	4F	130	1.42	1.02	0.035	0	JL6	1000
7740100169	4F	100	1.42	1.02	0.035	0	JR3.5	1000
7740110170	4F	110	1.42	1.02	0.035	0	JR3.5	1000
7740130171	4F	130	1.42	1.02	0.035	0	JR3.5	1000
7740100172	4F	100	1.42	1.02	0.035	0	JR4	1000
7740110173	4F	110	1.42	1.02	0.035	0	JR4	1000
7740130174	4F	130	1.42	1.02	0.035	0	JR4	1000
7740100175	4F	100	1.42	1.02	0.035	0	JR5	1000
7740110176	4F	110	1.42	1.02	0.035	0	JR5	1000
7740130177	4F	130	1.42	1.02	0.035	0	JR5	1000
7740100178	4F	100	1.42	1.02	0.035	0	JR6	1000
7740110179	4F	110	1.42	1.02	0.035	0	JR6	1000
7740130180	4F	130	1.42	1.02	0.035	0	JR6	1000
7740065181	4F	65	1.42	1.02	0.035	5/0.7	UNIV	1000
7740065182	4F	65	1.42	1.02	0.035	8/0.7	UNIV	1000
7740090183	4F	90	1.42	1.02	0.035	5/0.7	UNIV	1000
7740090184	4F	90	1.42	1.02	0.035	8/0.7	UNIV	1000
7740110185	4F	110	1.42	1.02	0.035	5/0.7	UNIV	1000
7740110186	4F	110	1.42	1.02	0.035	8/0.7	UNIV	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7740080187	4F	80	1.42	1.02	0.035	0	TRG	1000
7740080188	4F	80	1.42	1.02	0.035	1/0.7	TRG	1000
7740100189	4F	100	1.42	1.02	0.035	0	TRG	1000
7740100190	4F	100	1.42	1.02	0.035	1/0.7	TRG	1000
7740110191	4F	110	1.42	1.02	0.035	0	TRG	1000
7740110192	4F	110	1.42	1.02	0.035	1/0.7	TRG	1000
7740080193	4F	80	1.42	1.02	0.035	0	TRG 1	1000
7740080194	4F	80	1.42	1.02	0.035	2/0.7	TRG 1	1000
7740100195	4F	100	1.42	1.02	0.035	0	TRG 1	1000
7740100196	4F	100	1.42	1.02	0.035	2/0.7	TRG 1	1000
7740110197	4F	110	1.42	1.02	0.035	0	TRG 1	1000
7740110198	4F	110	1.42	1.02	0.035	2/0.7	TRG 1	1000
7740080199	4F	80	1.42	1.02	0.035	0	TRG 2	1000
7740080200	4F	80	1.42	1.02	0.035	1/0.7	TRG 2	1000
7740100201	4F	100	1.42	1.02	0.035	0	TRG 2	1000
7740100202	4F	100	1.42	1.02	0.035	1/0.7	TRG 2	1000
7740110203	4F	110	1.42	1.02	0.035	0	TRG 2	1000
7740110204	4F	110	1.42	1.02	0.035	1/0.7	TRG 2	1000
7750065001	5F	65	1.70	1.17	0.038	6/0.7	STRAIGHT	1000
7750065002	5F	65	1.70	1.17	0.038	0	STRAIGHT	1000
7750080003	5F	80	1.70	1.17	0.038	6/0.7	STRAIGHT	1000
7750080004	5F	80	1.70	1.17	0.038	0	STRAIGHT	1000
7750100005	5F	100	1.70	1.17	0.038	6/0.7	STRAIGHT	1000
7750100006	5F	100	1.70	1.17	0.038	0	STRAIGHT	1000
7750110007	5F	110	1.70	1.17	0.038	6/0.7	STRAIGHT	1000
7750110008	5F	110	1.70	1.17	0.038	0	STRAIGHT	1000
7750120009	5F	120	1.70	1.17	0.038	6/0.7	STRAIGHT	1000
7750120010	5F	120	1.70	1.17	0.038	0	STRAIGHT	1000
7750150011	5F	150	1.70	1.17	0.038	6/0.7	STRAIGHT	1000
7750150012	5F	150	1.70	1.17	0.038	0	STRAIGHT	1000
7750065013	5F	65	1.70	1.17	0.038	6/0.7	PIG	1000
7750080014	5F	80	1.70	1.17	0.038	6/0.7	PIG	1000
7750100015	5F	100	1.70	1.17	0.038	6/0.7	PIG	1000
7750110016	5F	110	1.70	1.17	0.038	6/0.7	PIG	1000
7750130017	5F	130	1.70	1.17	0.038	6/0.7	PIG	1000
7750065018	5F	65	1.70	1.17	0.038	8/0.7	PIG	1000
7750080019	5F	80	1.70	1.17	0.038	8/0.7	PIG	1000
7750100020	5F	100	1.70	1.17	0.038	8/0.7	PIG	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7750110021	5F	110	1.70	1.17	0.038	8/0.7	PIG	1000
7750130022	5F	130	1.70	1.17	0.038	8/0.7	PIG	1000
7750065023	5F	65	1.70	1.17	0.038	6/0.7	PIG-145°	1000
7750080024	5F	80	1.70	1.17	0.038	6/0.7	PIG-145°	1000
7750100025	5F	100	1.70	1.17	0.038	6/0.7	PIG-145°	1000
7750110026	5F	110	1.70	1.17	0.038	6/0.7	PIG-145°	1000
7750130027	5F	130	1.70	1.17	0.038	6/0.7	PIG-145°	1000
7750065028	5F	65	1.70	1.17	0.038	8/0.7	PIG-145°	1000
7750080029	5F	80	1.70	1.17	0.038	8/0.7	PIG-145°	1000
7750100030	5F	100	1.70	1.17	0.038	8/0.7	PIG-145°	1000
7750110031	5F	110	1.70	1.17	0.038	8/0.7	PIG-145°	1000
7750130032	5F	130	1.70	1.17	0.038	8/0.7	PIG-145°	1000
7750065033	5F	65	1.70	1.17	0.038	6/0.7	PIG-155°	1000
7750080034	5F	80	1.70	1.17	0.038	6/0.7	PIG-155°	1000
7750100035	5F	100	1.70	1.17	0.038	6/0.7	PIG-155°	1000
7750110036	5F	110	1.70	1.17	0.038	6/0.7	PIG-155°	1000
7750120037	5F	120	1.70	1.17	0.038	6/0.7	PIG-155°	1000
7750065038	5F	65	1.70	1.17	0.038	8/0.7	PIG-155°	1000
7750080039	5F	80	1.70	1.17	0.038	8/0.7	PIG-155°	1000
7750100040	5F	100	1.70	1.17	0.038	8/0.7	PIG-155°	1000
7750110041	5F	110	1.70	1.17	0.038	8/0.7	PIG-155°	1000
7750130042	5F	130	1.70	1.17	0.038	8/0.7	PIG-155°	1000
7750065043	5F	65	1.70	1.17	0.038	0	Vertebral	1000
7750100044	5F	100	1.70	1.17	0.038	0	Vertebral	1000
7750110045	5F	110	1.70	1.17	0.038	0	Vertebral	1000
7750065046	5F	65	1.70	1.17	0.038	2/0.7	MPA	1000
7750065047	5F	65	1.70	1.17	0.038	0	MPA	1000
7750080048	5F	80	1.70	1.17	0.038	2/0.7	MPA	1000
7750080049	5F	80	1.70	1.17	0.038	0	MPA	1000
7750100050	5F	100	1.70	1.17	0.038	2/0.7	MPA	1000
7750100051	5F	100	1.70	1.17	0.038	0	MPA	1000
7750125052	5F	125	1.70	1.17	0.038	2/0.7	MPA	1000
7750125053	5F	125	1.70	1.17	0.038	0	MPA	1000
7750065054	5F	65	1.70	1.17	0.038	2/0.7	MPB	1000
7750065055	5F	65	1.70	1.17	0.038	0	MPB	1000
7750080056	5F	80	1.70	1.17	0.038	2/0.7	MPB	1000
7750080057	5F	80	1.70	1.17	0.038	0	MPB	1000
7750100058	5F	100	1.70	1.17	0.038	2/0.7	MPB	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7750100059	5F	100	1.70	1.17	0.038	0	MPB	1000
7750125060	5F	125	1.70	1.17	0.038	2/0.7	MPB	1000
7750125061	5F	125	1.70	1.17	0.038	0	MPB	1000
7750065062	5F	65	1.70	1.17	0.038	2/0.7	MPC	1000
7750065063	5F	65	1.70	1.17	0.038	0	MPC	1000
7750080064	5F	80	1.70	1.17	0.038	2/0.7	MPC	1000
7750080065	5F	80	1.70	1.17	0.038	0	MPC	1000
7750100066	5F	100	1.70	1.17	0.038	2/0.7	MPC	1000
7750100067	5F	100	1.70	1.17	0.038	0	MPC	1000
7750125068	5F	125	1.70	1.17	0.038	2/0.7	MPC	1000
7750125069	5F	125	1.70	1.17	0.038	0	MPC	1000
7750065070	5F	65	1.70	1.17	0.038	2/0.7	MPD	1000
7750065071	5F	65	1.70	1.17	0.038	0	MPD	1000
7750080072	5F	80	1.70	1.17	0.038	2/0.7	MPD	1000
7750080073	5F	80	1.70	1.17	0.038	0	MPD	1000
7750100074	5F	100	1.70	1.17	0.038	2/0.7	MPD	1000
7750100075	5F	100	1.70	1.17	0.038	0	MPD	1000
7750125076	5F	125	1.70	1.17	0.038	2/0.7	MPD	1000
7750125077	5F	125	1.70	1.17	0.038	0	MPD	1000
7750065078	5F	65	1.70	1.17	0.038	2/0.7	MPE	1000
7750065079	5F	65	1.70	1.17	0.038	0	MPE	1000
7750080080	5F	80	1.70	1.17	0.038	2/0.7	MPE	1000
7750080081	5F	80	1.70	1.17	0.038	0	MPE	1000
7750100082	5F	100	1.70	1.17	0.038	2/0.7	MPE	1000
7750100083	5F	100	1.70	1.17	0.038	0	MPE	1000
7750125084	5F	125	1.70	1.17	0.038	2/0.7	MPE	1000
7750100085	5F	100	1.70	1.17	0.038	0	Mani	1000
7750100086	5F	100	1.70	1.17	0.038	0	Bentson I	1000
7750100087	5F	100	1.70	1.17	0.038	0	Bentson II	1000
7750100088	5F	100	1.70	1.17	0.038	0	Bentson III	1000
7750100089	5F	100	1.70	1.17	0.038	2/0.7	SIM I	1000
7750100090	5F	100	1.70	1.17	0.038	0	SIM I	1000
7750100091	5F	100	1.70	1.17	0.038	2/0.7	SIM II	1000
7750100092	5F	100	1.70	1.17	0.038	0	SIM II	1000
7750100093	5F	100	1.70	1.17	0.038	2/0.7	SIM III	1000
7750100094	5F	100	1.70	1.17	0.038	0	SIM III	1000
7750065095	5F	65	1.70	1.17	0.038	2/0.7	COBRA I	1000
7750065096	5F	65	1.70	1.17	0.038	0	COBRA I	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7750080097	5F	80	1.70	1.17	0.038	2/0.7	COBRA I	1000
7750080098	5F	80	1.70	1.17	0.038	0	COBRA I	1000
7750100099	5F	100	1.70	1.17	0.038	2/0.7	COBRA I	1000
7750100100	5F	100	1.70	1.17	0.038	0	COBRA I	1000
7750125101	5F	125	1.70	1.17	0.038	2/0.7	COBRA I	1000
7750125102	5F	125	1.70	1.17	0.038	0	COBRA I	1000
7750065103	5F	65	1.70	1.17	0.038	2/0.7	COBRA II	1000
7750065104	5F	65	1.70	1.17	0.038	0	COBRA II	1000
7750080105	5F	80	1.70	1.17	0.038	2/0.7	COBRA II	1000
7750080106	5F	80	1.70	1.17	0.038	0	COBRA II	1000
7750100107	5F	100	1.70	1.17	0.038	2/0.7	COBRA II	1000
7750100108	5F	100	1.70	1.17	0.038	0	COBRA II	1000
7750125109	5F	125	1.70	1.17	0.038	2/0.7	COBRA II	1000
7750125110	5F	125	1.70	1.17	0.038	0	COBRA II	1000
7750065111	5F	65	1.70	1.17	0.038	2/0.7	COBRA III	1000
7750065112	5F	65	1.70	1.17	0.038	0	COBRA III	1000
7750080113	5F	80	1.70	1.17	0.038	2/0.7	COBRA III	1000
7750080114	5F	80	1.70	1.17	0.038	0	COBRA III	1000
7750100115	5F	100	1.70	1.17	0.038	2/0.7	COBRA III	1000
7750100116	5F	100	1.70	1.17	0.038	0	COBRA III	1000
7750125117	5F	125	1.70	1.17	0.038	2/0.7	COBRA III	1000
7750125118	5F	125	1.70	1.17	0.038	0	COBRA III	1000
7750065119	5F	65	1.70	1.17	0.038	2/0.7	Renal small	1000
7750080120	5F	80	1.70	1.17	0.038	0	Renal small	1000
7750100121	5F	100	1.70	1.17	0.038	0	Renal small	1000
7750130122	5F	130	1.70	1.17	0.038	0	Renal small	1000
7750150123	5F	150	1.70	1.17	0.038	2/0.7	Renal small	1000
7750150124	5F	150	1.70	1.17	0.038	0	Renal small	1000
7750080125	5F	80	1.70	1.17	0.038	2/0.7	Renal Double	1000
7750080126	5F	80	1.70	1.17	0.038	0	Renal Double	1000
7750065127	5F	65	1.70	1.17	0.038	2/0.7	Renal Double	1000
7750065128	5F	65	1.70	1.17	0.038	0	Renal Double	1000
7750065129	5F	65	1.70	1.17	0.038	0	Shepherd Hook I	1000
7750065130	5F	65	1.70	1.17	0.038	0	Shepherd Hook II	1000
7750065131	5F	65	1.70	1.17	0.038	0	J-Curve I	1000
7750065132	5F	65	1.70	1.17	0.038	0	J-Curve II	1000
7750065133	5F	65	1.70	1.17	0.038	0	J-Curve III	1000
7750100134	5F	100	1.70	1.17	0.038	0	HeadHunter 1	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7750125135	5F	125	1.70	1.17	0.038	0	HeadHunter 2	1000
7750100136	5F	100	1.70	1.17	0.038	0	HeadHunter 2	1000
7750100137	5F	100	1.70	1.17	0.038	0	HeadHunter 3	1000
7750100138	5F	100	1.70	1.17	0.038	0	HeadHunter 5	1000
7750100139	5F	100	1.70	1.17	0.038	0	HeadHunter 6	1000
7750100140	5F	100	1.70	1.17	0.038	0	VTK	1000
7750125141	5F	125	1.70	1.17	0.038	0	VTK	1000
7750080142	5F	80	1.70	1.17	0.038	0	VS	1000
7750080143	5F	80	1.70	1.17	0.038	0	VS 1	1000
7750125144	5F	125	1.70	1.17	0.038	0	VS 1	1000
7750080145	5F	80	1.70	1.17	0.038	0	VS 2	1000
7750080146	5F	80	1.70	1.17	0.038	0	VS 3	1000
7750090147	5F	90	1.70	1.17	0.038	0	RUC	1000
7750070148	5F	70	1.70	1.17	0.038	0	Yashiro	1000
7750080149	5F	80	1.70	1.17	0.038	0	RH	1000
7750100150	5F	100	1.70	1.17	0.038	0	IM	1000
7750065151	5F	65	1.70	1.17	0.038	0	RLG	1000
7750100152	5F	100	1.70	1.17	0.038	0	RLG	1000
7750080153	5F	80	1.70	1.17	0.038	0	RS	1000
7750100154	5F	100	1.70	1.17	0.038	0	JL3.5	1000
7750110155	5F	110	1.70	1.17	0.038	0	JL3.5	1000
7750130156	5F	130	1.70	1.17	0.038	0	JL3.5	1000
7750100157	5F	100	1.70	1.17	0.038	0	JL4	1000
7750110158	5F	110	1.70	1.17	0.038	0	JL4	1000
7750130159	5F	130	1.70	1.17	0.038	0	JL4	1000
7750100160	5F	100	1.70	1.17	0.038	0	JL4.5	1000
7750110161	5F	110	1.70	1.17	0.038	0	JL4.5	1000
7750130162	5F	130	1.70	1.17	0.038	0	JL4.5	1000
7750100163	5F	100	1.70	1.17	0.038	0	JL5	1000
7750110164	5F	110	1.70	1.17	0.038	0	JL5	1000
7750130165	5F	130	1.70	1.17	0.038	0	JL5	1000
7750100166	5F	100	1.70	1.17	0.038	0	JL6	1000
7750110167	5F	110	1.70	1.17	0.038	0	JL6	1000
7750130168	5F	130	1.70	1.17	0.038	0	JL6	1000
7750100169	5F	100	1.70	1.17	0.038	0	JR3.5	1000
7750110170	5F	110	1.70	1.17	0.038	0	JR3.5	1000
7750130171	5F	130	1.70	1.17	0.038	0	JR3.5	1000
7750100172	5F	100	1.70	1.17	0.038	0	JR4	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7750110173	5F	110	1.70	1.17	0.038	0	JR4	1000
7750130174	5F	130	1.70	1.17	0.038	0	JR4	1000
7750100175	5F	100	1.70	1.17	0.038	0	JR5	1000
7750110176	5F	110	1.70	1.17	0.038	0	JR5	1000
7750130177	5F	130	1.70	1.17	0.038	0	JR5	1000
7750100178	5F	100	1.70	1.17	0.038	0	JR6	1000
7750110179	5F	110	1.70	1.17	0.038	0	JR6	1000
7750130180	5F	130	1.70	1.17	0.038	0	JR6	1000
7750065181	5F	65	1.70	1.17	0.038	5/0.7	UNIV	1000
7750065182	5F	65	1.70	1.17	0.038	8/0.7	UNIV	1000
7750090183	5F	90	1.70	1.17	0.038	5/0.7	UNIV	1000
7750090184	5F	90	1.70	1.17	0.038	8/0.7	UNIV	1000
7750110185	5F	110	1.70	1.17	0.038	5/0.7	UNIV	1000
7750110186	5F	110	1.70	1.17	0.038	8/0.7	UNIV	1000
7750080187	5F	80	1.70	1.17	0.038	0	TRG	1000
7750080188	5F	80	1.70	1.17	0.038	1/0.7	TRG	1000
7750100189	5F	100	1.70	1.17	0.038	0	TRG	1000
7750100190	5F	100	1.70	1.17	0.038	1/0.7	TRG	1000
7750110191	5F	110	1.70	1.17	0.038	0	TRG	1000
7750110192	5F	110	1.70	1.17	0.038	1/0.7	TRG	1000
7750080193	5F	80	1.70	1.17	0.038	0	TRG 1	1000
7750080194	5F	80	1.70	1.17	0.038	2/0.7	TRG 1	1000
7750100195	5F	100	1.70	1.17	0.038	0	TRG 1	1000
7750100196	5F	100	1.70	1.17	0.038	2/0.7	TRG 1	1000
7750110197	5F	110	1.70	1.17	0.038	0	TRG 1	1000
7750110198	5F	110	1.70	1.17	0.038	2/0.7	TRG 1	1000
7750080199	5F	80	1.70	1.17	0.038	0	TRG 2	1000
7750080200	5F	80	1.70	1.17	0.038	1/0.7	TRG 2	1000
7750100201	5F	100	1.70	1.17	0.038	0	TRG 2	1000
7750100202	5F	100	1.70	1.17	0.038	1/0.7	TRG 2	1000
7750110203	5F	110	1.70	1.17	0.038	0	TRG 2	1000
7750110204	5F	110	1.70	1.17	0.038	1/0.7	TRG 2	1000
7755065001	5.5F	65	1.85	1.24	0.038	6/0.7	STRAIGHT	1000
7755065002	5.5F	65	1.85	1.24	0.038	0	STRAIGHT	1000
7755080003	5.5F	80	1.85	1.24	0.038	6/0.7	STRAIGHT	1000
7755080004	5.5F	80	1.85	1.24	0.038	0	STRAIGHT	1000
7755100005	5.5F	100	1.85	1.24	0.038	6/0.7	STRAIGHT	1000
7755100006	5.5F	100	1.85	1.24	0.038	0	STRAIGHT	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7755110007	5.5F	110	1.85	1.24	0.038	6/0.7	STRAIGHT	1000
7755110008	5.5F	110	1.85	1.24	0.038	0	STRAIGHT	1000
7755120009	5.5F	120	1.85	1.24	0.038	6/0.7	STRAIGHT	1000
7755120010	5.5F	120	1.85	1.24	0.038	0	STRAIGHT	1000
7755150011	5.5F	150	1.85	1.24	0.038	6/0.7	STRAIGHT	1000
7755150012	5.5F	150	1.85	1.24	0.038	0	STRAIGHT	1000
7755065013	5.5F	65	1.85	1.24	0.038	6/0.7	PIG	1000
7755080014	5.5F	80	1.85	1.24	0.038	6/0.7	PIG	1000
7755100015	5.5F	100	1.85	1.24	0.038	6/0.7	PIG	1000
7755110016	5.5F	110	1.85	1.24	0.038	6/0.7	PIG	1000
7755130017	5.5F	130	1.85	1.24	0.038	6/0.7	PIG	1000
7755065018	5.5F	65	1.85	1.24	0.038	8/0.7	PIG	1000
7755080019	5.5F	80	1.85	1.24	0.038	8/0.7	PIG	1000
7755100020	5.5F	100	1.85	1.24	0.038	8/0.7	PIG	1000
7755110021	5.5F	110	1.85	1.24	0.038	8/0.7	PIG	1000
7755130022	5.5F	130	1.85	1.24	0.038	8/0.7	PIG	1000
7755065023	5.5F	65	1.85	1.24	0.038	6/0.7	PIG-145°	1000
7755080024	5.5F	80	1.85	1.24	0.038	6/0.7	PIG-145°	1000
7755100025	5.5F	100	1.85	1.24	0.038	6/0.7	PIG-145°	1000
7755110026	5.5F	110	1.85	1.24	0.038	6/0.7	PIG-145°	1000
7755130027	5.5F	130	1.85	1.24	0.038	6/0.7	PIG-145°	1000
7755065028	5.5F	65	1.85	1.24	0.038	8/0.7	PIG-145°	1000
7755080029	5.5F	80	1.85	1.24	0.038	8/0.7	PIG-145°	1000
7755100030	5.5F	100	1.85	1.24	0.038	8/0.7	PIG-145°	1000
7755110031	5.5F	110	1.85	1.24	0.038	8/0.7	PIG-145°	1000
7755130032	5.5F	130	1.85	1.24	0.038	8/0.7	PIG-145°	1000
7755065033	5.5F	65	1.85	1.24	0.038	6/0.7	PIG-155°	1000
7755080034	5.5F	80	1.85	1.24	0.038	6/0.7	PIG-155°	1000
7755100035	5.5F	100	1.85	1.24	0.038	6/0.7	PIG-155°	1000
7755110036	5.5F	110	1.85	1.24	0.038	6/0.7	PIG-155°	1000
7755120037	5.5F	120	1.85	1.24	0.038	6/0.7	PIG-155°	1000
7755065038	5.5F	65	1.85	1.24	0.038	8/0.7	PIG-155°	1000
7755080039	5.5F	80	1.85	1.24	0.038	8/0.7	PIG-155°	1000
7755100040	5.5F	100	1.85	1.24	0.038	8/0.7	PIG-155°	1000
7755110041	5.5F	110	1.85	1.24	0.038	8/0.7	PIG-155°	1000
7755130042	5.5F	130	1.85	1.24	0.038	8/0.7	PIG-155°	1000
7755065043	5.5F	65	1.85	1.24	0.038	0	Vertebral	1000
7755100044	5.5F	100	1.85	1.24	0.038	0	Vertebral	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7755110045	5.5F	110	1.85	1.24	0.038	0	Vertebral	1000
7755065046	5.5F	65	1.85	1.24	0.038	2/0.7	MPA	1000
7755065047	5.5F	65	1.85	1.24	0.038	0	MPA	1000
7755080048	5.5F	80	1.85	1.24	0.038	2/0.7	MPA	1000
7755080049	5.5F	80	1.85	1.24	0.038	0	MPA	1000
7755100050	5.5F	100	1.85	1.24	0.038	2/0.7	MPA	1000
7755100051	5.5F	100	1.85	1.24	0.038	0	MPA	1000
7755125052	5.5F	125	1.85	1.24	0.038	2/0.7	MPA	1000
7755125053	5.5F	125	1.85	1.24	0.038	0	MPA	1000
7755065054	5.5F	65	1.85	1.24	0.038	2/0.7	MPB	1000
7755065055	5.5F	65	1.85	1.24	0.038	0	MPB	1000
7755080056	5.5F	80	1.85	1.24	0.038	2/0.7	MPB	1000
7755080057	5.5F	80	1.85	1.24	0.038	0	MPB	1000
7755100058	5.5F	100	1.85	1.24	0.038	2/0.7	MPB	1000
7755100059	5.5F	100	1.85	1.24	0.038	0	MPB	1000
7755125060	5.5F	125	1.85	1.24	0.038	2/0.7	MPB	1000
7755125061	5.5F	125	1.85	1.24	0.038	0	MPB	1000
7755065062	5.5F	65	1.85	1.24	0.038	2/0.7	MPC	1000
7755065063	5.5F	65	1.85	1.24	0.038	0	MPC	1000
7755080064	5.5F	80	1.85	1.24	0.038	2/0.7	MPC	1000
7755080065	5.5F	80	1.85	1.24	0.038	0	MPC	1000
7755100066	5.5F	100	1.85	1.24	0.038	2/0.7	MPC	1000
7755100067	5.5F	100	1.85	1.24	0.038	0	MPC	1000
7755125068	5.5F	125	1.85	1.24	0.038	2/0.7	MPC	1000
7755125069	5.5F	125	1.85	1.24	0.038	0	MPC	1000
7755065070	5.5F	65	1.85	1.24	0.038	2/0.7	MPD	1000
7755065071	5.5F	65	1.85	1.24	0.038	0	MPD	1000
7755080072	5.5F	80	1.85	1.24	0.038	2/0.7	MPD	1000
7755080073	5.5F	80	1.85	1.24	0.038	0	MPD	1000
7755100074	5.5F	100	1.85	1.24	0.038	2/0.7	MPD	1000
7755100075	5.5F	100	1.85	1.24	0.038	0	MPD	1000
7755125076	5.5F	125	1.85	1.24	0.038	2/0.7	MPD	1000
7755125077	5.5F	125	1.85	1.24	0.038	0	MPD	1000
7755065078	5.5F	65	1.85	1.24	0.038	2/0.7	MPE	1000
7755065079	5.5F	65	1.85	1.24	0.038	0	MPE	1000
7755080080	5.5F	80	1.85	1.24	0.038	2/0.7	MPE	1000
7755080081	5.5F	80	1.85	1.24	0.038	0	MPE	1000
7755100082	5.5F	100	1.85	1.24	0.038	2/0.7	MPE	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7755100083	5.5F	100	1.85	1.24	0.038	0	MPE	1000
7755125084	5.5F	125	1.85	1.24	0.038	2/0.7	MPE	1000
7755100085	5.5F	100	1.85	1.24	0.038	0	Mani	1000
7755100086	5.5F	100	1.85	1.24	0.038	0	Bentson I	1000
7755100087	5.5F	100	1.85	1.24	0.038	0	Bentson II	1000
7755100088	5.5F	100	1.85	1.24	0.038	0	Bentson III	1000
7755100089	5.5F	100	1.85	1.24	0.038	2/0.7	SIM I	1000
7755100090	5.5F	100	1.85	1.24	0.038	0	SIM I	1000
7755100091	5.5F	100	1.85	1.24	0.038	2/0.7	SIM II	1000
7755100092	5.5F	100	1.85	1.24	0.038	0	SIM II	1000
7755100093	5.5F	100	1.85	1.24	0.038	2/0.7	SIM III	1000
7755100094	5.5F	100	1.85	1.24	0.038	0	SIM III	1000
7755065095	5.5F	65	1.85	1.24	0.038	2/0.7	COBRA I	1000
7755065096	5.5F	65	1.85	1.24	0.038	0	COBRA I	1000
7755080097	5.5F	80	1.85	1.24	0.038	2/0.7	COBRA I	1000
7755080098	5.5F	80	1.85	1.24	0.038	0	COBRA I	1000
7755100099	5.5F	100	1.85	1.24	0.038	2/0.7	COBRA I	1000
7755100100	5.5F	100	1.85	1.24	0.038	0	COBRA I	1000
7755125101	5.5F	125	1.85	1.24	0.038	2/0.7	COBRA I	1000
7755125102	5.5F	125	1.85	1.24	0.038	0	COBRA I	1000
7755065103	5.5F	65	1.85	1.24	0.038	2/0.7	COBRA II	1000
7755065104	5.5F	65	1.85	1.24	0.038	0	COBRA II	1000
7755080105	5.5F	80	1.85	1.24	0.038	2/0.7	COBRA II	1000
7755080106	5.5F	80	1.85	1.24	0.038	0	COBRA II	1000
7755100107	5.5F	100	1.85	1.24	0.038	2/0.7	COBRA II	1000
7755100108	5.5F	100	1.85	1.24	0.038	0	COBRA II	1000
7755125109	5.5F	125	1.85	1.24	0.038	2/0.7	COBRA II	1000
7755125110	5.5F	125	1.85	1.24	0.038	0	COBRA II	1000
7755065111	5.5F	65	1.85	1.24	0.038	2/0.7	COBRA III	1000
7755065112	5.5F	65	1.85	1.24	0.038	0	COBRA III	1000
7755080113	5.5F	80	1.85	1.24	0.038	2/0.7	COBRA III	1000
7755080114	5.5F	80	1.85	1.24	0.038	0	COBRA III	1000
7755100115	5.5F	100	1.85	1.24	0.038	2/0.7	COBRA III	1000
7755100116	5.5F	100	1.85	1.24	0.038	0	COBRA III	1000
7755125117	5.5F	125	1.85	1.24	0.038	2/0.7	COBRA III	1000
7755125118	5.5F	125	1.85	1.24	0.038	0	COBRA III	1000
7755065119	5.5F	65	1.85	1.24	0.038	2/0.7	Renal small	1000
7755080120	5.5F	80	1.85	1.24	0.038	0	Renal small	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7755100121	5.5F	100	1.85	1.24	0.038	0	Renal small	1000
7755130122	5.5F	130	1.85	1.24	0.038	0	Renal small	1000
7755150123	5.5F	150	1.85	1.24	0.038	2/0.7	Renal small	1000
7755150124	5.5F	150	1.85	1.24	0.038	0	Renal small	1000
7755080125	5.5F	80	1.85	1.24	0.038	2/0.7	Renal Double	1000
7755080126	5.5F	80	1.85	1.24	0.038	0	Renal Double	1000
7755065127	5.5F	65	1.85	1.24	0.038	2/0.7	Renal Double	1000
7755065128	5.5F	65	1.85	1.24	0.038	0	Renal Double	1000
7755065129	5.5F	65	1.85	1.24	0.038	0	Shepherd Hook I	1000
7755065130	5.5F	65	1.85	1.24	0.038	0	Shepherd Hook II	1000
7755065131	5.5F	65	1.85	1.24	0.038	0	J-Curve I	1000
7755065132	5.5F	65	1.85	1.24	0.038	0	J-Curve II	1000
7755065133	5.5F	65	1.85	1.24	0.038	0	J-Curve III	1000
7755100134	5.5F	100	1.85	1.24	0.038	0	HeadHunter 1	1000
7755125135	5.5F	125	1.85	1.24	0.038	0	HeadHunter 2	1000
7755100136	5.5F	100	1.85	1.24	0.038	0	HeadHunter 2	1000
7755100137	5.5F	100	1.85	1.24	0.038	0	HeadHunter 3	1000
7755100138	5.5F	100	1.85	1.24	0.038	0	HeadHunter 5	1000
7755100139	5.5F	100	1.85	1.24	0.038	0	HeadHunter 6	1000
7755100140	5.5F	100	1.85	1.24	0.038	0	VTK	1000
7755125141	5.5F	125	1.85	1.24	0.038	0	VTK	1000
7755080142	5.5F	80	1.85	1.24	0.038	0	VS	1000
7755080143	5.5F	80	1.85	1.24	0.038	0	VS 1	1000
7755125144	5.5F	125	1.85	1.24	0.038	0	VS 1	1000
7755080145	5.5F	80	1.85	1.24	0.038	0	VS 2	1000
7755080146	5.5F	80	1.85	1.24	0.038	0	VS 3	1000
7755090147	5.5F	90	1.85	1.24	0.038	0	RUC	1000
7755070148	5.5F	70	1.85	1.24	0.038	0	Yashiro	1000
7755080149	5.5F	80	1.85	1.24	0.038	0	RH	1000
7755100150	5.5F	100	1.85	1.24	0.038	0	IM	1000
7755065151	5.5F	65	1.85	1.24	0.038	0	RLG	1000
7755100152	5.5F	100	1.85	1.24	0.038	0	RLG	1000
7755080153	5.5F	80	1.85	1.24	0.038	0	RS	1000
7755100154	5.5F	100	1.85	1.24	0.038	0	JL3.5	1000
7755110155	5.5F	110	1.85	1.24	0.038	0	JL3.5	1000
7755130156	5.5F	130	1.85	1.24	0.038	0	JL3.5	1000
7755100157	5.5F	100	1.85	1.24	0.038	0	JL4	1000
7755110158	5.5F	110	1.85	1.24	0.038	0	JL4	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7755130159	5.5F	130	1.85	1.24	0.038	0	JL4	1000
7755100160	5.5F	100	1.85	1.24	0.038	0	JL4.5	1000
7755110161	5.5F	110	1.85	1.24	0.038	0	JL4.5	1000
7755130162	5.5F	130	1.85	1.24	0.038	0	JL4.5	1000
7755100163	5.5F	100	1.85	1.24	0.038	0	JL5	1000
7755110164	5.5F	110	1.85	1.24	0.038	0	JL5	1000
7755130165	5.5F	130	1.85	1.24	0.038	0	JL5	1000
7755100166	5.5F	100	1.85	1.24	0.038	0	JL6	1000
7755110167	5.5F	110	1.85	1.24	0.038	0	JL6	1000
7755130168	5.5F	130	1.85	1.24	0.038	0	JL6	1000
7755100169	5.5F	100	1.85	1.24	0.038	0	JR3.5	1000
7755110170	5.5F	110	1.85	1.24	0.038	0	JR3.5	1000
7755130171	5.5F	130	1.85	1.24	0.038	0	JR3.5	1000
7755100172	5.5F	100	1.85	1.24	0.038	0	JR4	1000
7755110173	5.5F	110	1.85	1.24	0.038	0	JR4	1000
7755130174	5.5F	130	1.85	1.24	0.038	0	JR4	1000
7755100175	5.5F	100	1.85	1.24	0.038	0	JR5	1000
7755110176	5.5F	110	1.85	1.24	0.038	0	JR5	1000
7755130177	5.5F	130	1.85	1.24	0.038	0	JR5	1000
7755100178	5.5F	100	1.85	1.24	0.038	0	JR6	1000
7755110179	5.5F	110	1.85	1.24	0.038	0	JR6	1000
7755130180	5.5F	130	1.85	1.24	0.038	0	JR6	1000
7755065181	5.5F	65	1.85	1.24	0.038	5/0.7	UNIV	1000
7755065182	5.5F	65	1.85	1.24	0.038	8/0.7	UNIV	1000
7755090183	5.5F	90	1.85	1.24	0.038	5/0.7	UNIV	1000
7755090184	5.5F	90	1.85	1.24	0.038	8/0.7	UNIV	1000
7755110185	5.5F	110	1.85	1.24	0.038	5/0.7	UNIV	1000
7755110186	5.5F	110	1.85	1.24	0.038	8/0.7	UNIV	1000
7755080187	5.5F	80	1.85	1.24	0.038	0	TRG	1000
7755080188	5.5F	80	1.85	1.24	0.038	1/0.7	TRG	1000
7755100189	5.5F	100	1.85	1.24	0.038	0	TRG	1000
7755100190	5.5F	100	1.85	1.24	0.038	1/0.7	TRG	1000
7755110191	5.5F	110	1.85	1.24	0.038	0	TRG	1000
7755110192	5.5F	110	1.85	1.24	0.038	1/0.7	TRG	1000
7755080193	5.5F	80	1.85	1.24	0.038	0	TRG 1	1000
7755080194	5.5F	80	1.85	1.24	0.038	2/0.7	TRG 1	1000
7755100195	5.5F	100	1.85	1.24	0.038	0	TRG 1	1000
7755100196	5.5F	100	1.85	1.24	0.038	2/0.7	TRG 1	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7755110197	5.5F	110	1.85	1.24	0.038	0	TRG 1	1000
7755110198	5.5F	110	1.85	1.24	0.038	2/0.7	TRG 1	1000
7755080199	5.5F	80	1.85	1.24	0.038	0	TRG 2	1000
7755080200	5.5F	80	1.85	1.24	0.038	1/0.7	TRG 2	1000
7755100201	5.5F	100	1.85	1.24	0.038	0	TRG 2	1000
7755100202	5.5F	100	1.85	1.24	0.038	1/0.7	TRG 2	1000
7755110203	5.5F	110	1.85	1.24	0.038	0	TRG 2	1000
7755110204	5.5F	110	1.85	1.24	0.038	1/0.7	TRG 2	1000
7760065001	6F	65	2.00	1.30	0.038	6/0.7	STRAIGHT	1000
7760065002	6F	65	2.00	1.30	0.038	0	STRAIGHT	1000
7760080003	6F	80	2.00	1.30	0.038	6/0.7	STRAIGHT	1000
7760080004	6F	80	2.00	1.30	0.038	0	STRAIGHT	1000
7760100005	6F	100	2.00	1.30	0.038	6/0.7	STRAIGHT	1000
7760100006	6F	100	2.00	1.30	0.038	0	STRAIGHT	1000
7760110007	6F	110	2.00	1.30	0.038	6/0.7	STRAIGHT	1000
7760110008	6F	110	2.00	1.30	0.038	0	STRAIGHT	1000
7760120009	6F	120	2.00	1.30	0.038	6/0.7	STRAIGHT	1000
7760120010	6F	120	2.00	1.30	0.038	0	STRAIGHT	1000
7760150011	6F	150	2.00	1.30	0.038	6/0.7	STRAIGHT	1000
7760150012	6F	150	2.00	1.30	0.038	0	STRAIGHT	1000
7760065013	6F	65	2.00	1.30	0.038	6/0.7	PIG	1000
7760080014	6F	80	2.00	1.30	0.038	6/0.7	PIG	1000
7760100015	6F	100	2.00	1.30	0.038	6/0.7	PIG	1000
7760110016	6F	110	2.00	1.30	0.038	6/0.7	PIG	1000
7760130017	6F	130	2.00	1.30	0.038	6/0.7	PIG	1000
7760065018	6F	65	2.00	1.30	0.038	8/0.7	PIG	1000
7760080019	6F	80	2.00	1.30	0.038	8/0.7	PIG	1000
7760100020	6F	100	2.00	1.30	0.038	8/0.7	PIG	1000
7760110021	6F	110	2.00	1.30	0.038	8/0.7	PIG	1000
7760130022	6F	130	2.00	1.30	0.038	8/0.7	PIG	1000
7760065023	6F	65	2.00	1.30	0.038	6/0.7	PIG-145°	1000
7760080024	6F	80	2.00	1.30	0.038	6/0.7	PIG-145°	1000
7760100025	6F	100	2.00	1.30	0.038	6/0.7	PIG-145°	1000
7760110026	6F	110	2.00	1.30	0.038	6/0.7	PIG-145°	1000
7760130027	6F	130	2.00	1.30	0.038	6/0.7	PIG-145°	1000
7760065028	6F	65	2.00	1.30	0.038	8/0.7	PIG-145°	1000
7760080029	6F	80	2.00	1.30	0.038	8/0.7	PIG-145°	1000
7760100030	6F	100	2.00	1.30	0.038	8/0.7	PIG-145°	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7760110031	6F	110	2.00	1.30	0.038	8/0.7	PIG-145°	1000
7760130032	6F	130	2.00	1.30	0.038	8/0.7	PIG-145°	1000
7760065033	6F	65	2.00	1.30	0.038	6/0.7	PIG-155°	1000
7760080034	6F	80	2.00	1.30	0.038	6/0.7	PIG-155°	1000
7760100035	6F	100	2.00	1.30	0.038	6/0.7	PIG-155°	1000
7760110036	6F	110	2.00	1.30	0.038	6/0.7	PIG-155°	1000
7760130037	6F	130	2.00	1.30	0.038	6/0.7	PIG-155°	1000
7760065038	6F	65	2.00	1.30	0.038	8/0.7	PIG-155°	1000
7760080039	6F	80	2.00	1.30	0.038	8/0.7	PIG-155°	1000
7760100040	6F	100	2.00	1.30	0.038	8/0.7	PIG-155°	1000
7760110041	6F	110	2.00	1.30	0.038	8/0.7	PIG-155°	1000
7760120042	6F	120	2.00	1.30	0.038	8/0.7	PIG-155°	1000
7760065043	6F	65	2.00	1.30	0.038	0	Vertebral	1000
7760100044	6F	100	2.00	1.30	0.038	0	Vertebral	1000
7760110045	6F	110	2.00	1.30	0.038	0	Vertebral	1000
7760065046	6F	65	2.00	1.30	0.038	2/0.7	MPA	1000
7760065047	6F	65	2.00	1.30	0.038	0	MPA	1000
7760080048	6F	80	2.00	1.30	0.038	2/0.7	MPA	1000
7760080049	6F	80	2.00	1.30	0.038	0	MPA	1000
7760100050	6F	100	2.00	1.30	0.038	2/0.7	MPA	1000
7760100051	6F	100	2.00	1.30	0.038	0	MPA	1000
7760125052	6F	125	2.00	1.30	0.038	2/0.7	MPA	1000
7760125053	6F	125	2.00	1.30	0.038	0	MPA	1000
7760065054	6F	65	2.00	1.30	0.038	2/0.7	MPB	1000
7760065055	6F	65	2.00	1.30	0.038	0	MPB	1000
7760080056	6F	80	2.00	1.30	0.038	2/0.7	MPB	1000
7760080057	6F	80	2.00	1.30	0.038	0	MPB	1000
7760100058	6F	100	2.00	1.30	0.038	2/0.7	MPB	1000
7760100059	6F	100	2.00	1.30	0.038	0	MPB	1000
7760125060	6F	125	2.00	1.30	0.038	2/0.7	MPB	1000
7760125061	6F	125	2.00	1.30	0.038	0	MPB	1000
7760065062	6F	65	2.00	1.30	0.038	2/0.7	MPC	1000
7760065063	6F	65	2.00	1.30	0.038	0	MPC	1000
7760080064	6F	80	2.00	1.30	0.038	2/0.7	MPC	1000
7760080065	6F	80	2.00	1.30	0.038	0	MPC	1000
7760100066	6F	100	2.00	1.30	0.038	2/0.7	MPC	1000
7760100067	6F	100	2.00	1.30	0.038	0	MPC	1000
7760125068	6F	125	2.00	1.30	0.038	2/0.7	MPC	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7760125069	6F	125	2.00	1.30	0.038	0	MPC	1000
7760065070	6F	65	2.00	1.30	0.038	2/0.7	MPD	1000
7760065071	6F	65	2.00	1.30	0.038	0	MPD	1000
7760080072	6F	80	2.00	1.30	0.038	2/0.7	MPD	1000
7760080073	6F	80	2.00	1.30	0.038	0	MPD	1000
7760100074	6F	100	2.00	1.30	0.038	2/0.7	MPD	1000
7760100075	6F	100	2.00	1.30	0.038	0	MPD	1000
7760125076	6F	125	2.00	1.30	0.038	2/0.7	MPD	1000
7760125077	6F	125	2.00	1.30	0.038	0	MPD	1000
7760065078	6F	65	2.00	1.30	0.038	2/0.7	MPE	1000
7760065079	6F	65	2.00	1.30	0.038	0	MPE	1000
7760080080	6F	80	2.00	1.30	0.038	2/0.7	MPE	1000
7760080081	6F	80	2.00	1.30	0.038	0	MPE	1000
7760100082	6F	100	2.00	1.30	0.038	2/0.7	MPE	1000
7760100083	6F	100	2.00	1.30	0.038	0	MPE	1000
7760125084	6F	125	2.00	1.30	0.038	2/0.7	MPE	1000
7760100085	6F	100	2.00	1.30	0.038	0	Mani	1000
7760100086	6F	100	2.00	1.30	0.038	0	Bentson I	1000
7760100087	6F	100	2.00	1.30	0.038	0	Bentson II	1000
7760100088	6F	100	2.00	1.30	0.038	0	Bentson III	1000
7760100089	6F	100	2.00	1.30	0.038	2/0.7	SIM I	1000
7760100090	6F	100	2.00	1.30	0.038	0	SIM I	1000
7760100091	6F	100	2.00	1.30	0.038	2/0.7	SIM II	1000
7760100092	6F	100	2.00	1.30	0.038	0	SIM II	1000
7760100093	6F	100	2.00	1.30	0.038	2/0.7	SIM III	1000
7760100094	6F	100	2.00	1.30	0.038	0	SIM III	1000
7760065095	6F	65	2.00	1.30	0.038	2/0.7	COBRA I	1000
7760065096	6F	65	2.00	1.30	0.038	0	COBRA I	1000
7760080097	6F	80	2.00	1.30	0.038	2/0.7	COBRA I	1000
7760080098	6F	80	2.00	1.30	0.038	0	COBRA I	1000
7760100099	6F	100	2.00	1.30	0.038	2/0.7	COBRA I	1000
7760100100	6F	100	2.00	1.30	0.038	0	COBRA I	1000
7760125101	6F	125	2.00	1.30	0.038	2/0.7	COBRA I	1000
7760125102	6F	125	2.00	1.30	0.038	0	COBRA I	1000
7760065103	6F	65	2.00	1.30	0.038	2/0.7	COBRA II	1000
7760065104	6F	65	2.00	1.30	0.038	0	COBRA II	1000
7760080105	6F	80	2.00	1.30	0.038	2/0.7	COBRA II	1000
7760080106	6F	80	2.00	1.30	0.038	0	COBRA II	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7760100107	6F	100	2.00	1.30	0.038	2/0.7	COBRA II	1000
7760100108	6F	100	2.00	1.30	0.038	0	COBRA II	1000
7760125109	6F	125	2.00	1.30	0.038	2/0.7	COBRA II	1000
7760125110	6F	125	2.00	1.30	0.038	0	COBRA II	1000
7760065111	6F	65	2.00	1.30	0.038	2/0.7	COBRA III	1000
7760065112	6F	65	2.00	1.30	0.038	0	COBRA III	1000
7760080113	6F	80	2.00	1.30	0.038	2/0.7	COBRA III	1000
7760080114	6F	80	2.00	1.30	0.038	0	COBRA III	1000
7760100115	6F	100	2.00	1.30	0.038	2/0.7	COBRA III	1000
7760100116	6F	100	2.00	1.30	0.038	0	COBRA III	1000
7760125117	6F	125	2.00	1.30	0.038	2/0.7	COBRA III	1000
7760125118	6F	125	2.00	1.30	0.038	0	COBRA III	1000
7760065119	6F	65	2.00	1.30	0.038	2/0.7	Renal small	1000
7760080120	6F	80	2.00	1.30	0.038	0	Renal small	1000
7760100121	6F	100	2.00	1.30	0.038	0	Renal small	1000
7760130122	6F	130	2.00	1.30	0.038	0	Renal small	1000
7760150123	6F	150	2.00	1.30	0.038	2/0.7	Renal small	1000
7760150124	6F	150	2.00	1.30	0.038	0	Renal small	1000
7760080125	6F	80	2.00	1.30	0.038	2/0.7	Renal Double	1000
7760080126	6F	80	2.00	1.30	0.038	0	Renal Double	1000
7760065127	6F	65	2.00	1.30	0.038	2/0.7	Renal Double	1000
7760065128	6F	65	2.00	1.30	0.038	0	Renal Double	1000
7760065129	6F	65	2.00	1.30	0.038	0	Shepherd Hook I	1000
7760065130	6F	65	2.00	1.30	0.038	0	Shepherd Hook II	1000
7760065131	6F	65	2.00	1.30	0.038	0	J-Curve I	1000
7760065132	6F	65	2.00	1.30	0.038	0	J-Curve II	1000
7760065133	6F	65	2.00	1.30	0.038	0	J-Curve III	1000
7760100134	6F	100	2.00	1.30	0.038	0	HeadHunter 1	1000
7760125135	6F	125	2.00	1.30	0.038	0	HeadHunter 2	1000
7760100136	6F	100	2.00	1.30	0.038	0	HeadHunter 2	1000
7760100137	6F	100	2.00	1.30	0.038	0	HeadHunter 3	1000
7760100138	6F	100	2.00	1.30	0.038	0	HeadHunter 5	1000
7760100139	6F	100	2.00	1.30	0.038	0	HeadHunter 6	1000
7760100140	6F	100	2.00	1.30	0.038	0	VTK	1000
7760125141	6F	125	2.00	1.30	0.038	0	VTK	1000
7760080142	6F	80	2.00	1.30	0.038	0	VS	1000
7760080143	6F	80	2.00	1.30	0.038	0	VS 1	1000
7760125144	6F	125	2.00	1.30	0.038	0	VS 1	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7760080145	6F	80	2.00	1.30	0.038	0	VS 2	1000
7760080146	6F	80	2.00	1.30	0.038	0	VS 3	1000
7760090147	6F	90	2.00	1.30	0.038	0	RUC	1000
7760070148	6F	70	2.00	1.30	0.038	0	Yashiro	1000
7760080149	6F	80	2.00	1.30	0.038	0	RH	1000
7760100150	6F	100	2.00	1.30	0.038	0	IM	1000
7760065151	6F	65	2.00	1.30	0.038	0	RLG	1000
7760100152	6F	100	2.00	1.30	0.038	0	RLG	1000
7760080153	6F	80	2.00	1.30	0.038	0	RS	1000
7760100154	6F	100	2.00	1.30	0.038	0	JL3.5	1000
7760110155	6F	110	2.00	1.30	0.038	0	JL3.5	1000
7760130156	6F	130	2.00	1.30	0.038	0	JL3.5	1000
7760100157	6F	100	2.00	1.30	0.038	0	JL4	1000
7760110158	6F	110	2.00	1.30	0.038	0	JL4	1000
7760130159	6F	130	2.00	1.30	0.038	0	JL4	1000
7760100160	6F	100	2.00	1.30	0.038	0	JL4.5	1000
7760110161	6F	110	2.00	1.30	0.038	0	JL4.5	1000
7760130162	6F	130	2.00	1.30	0.038	0	JL4.5	1000
7760100163	6F	100	2.00	1.30	0.038	0	JL5	1000
7760110164	6F	110	2.00	1.30	0.038	0	JL5	1000
7760130165	6F	130	2.00	1.30	0.038	0	JL5	1000
7760100166	6F	100	2.00	1.30	0.038	0	JL6	1000
7760110167	6F	110	2.00	1.30	0.038	0	JL6	1000
7760130168	6F	130	2.00	1.30	0.038	0	JL6	1000
7760100169	6F	100	2.00	1.30	0.038	0	JR3.5	1000
7760110170	6F	110	2.00	1.30	0.038	0	JR3.5	1000
7760130171	6F	130	2.00	1.30	0.038	0	JR3.5	1000
7760100172	6F	100	2.00	1.30	0.038	0	JR4	1000
7760110173	6F	110	2.00	1.30	0.038	0	JR4	1000
7760130174	6F	130	2.00	1.30	0.038	0	JR4	1000
7760100175	6F	100	2.00	1.30	0.038	0	JR5	1000
7760110176	6F	110	2.00	1.30	0.038	0	JR5	1000
7760130177	6F	130	2.00	1.30	0.038	0	JR5	1000
7760100178	6F	100	2.00	1.30	0.038	0	JR6	1000
7760110179	6F	110	2.00	1.30	0.038	0	JR6	1000
7760130180	6F	130	2.00	1.30	0.038	0	JR6	1000
7760065181	6F	65	2.00	1.30	0.038	5/0.7	UNIV	1000
7760065182	6F	65	2.00	1.30	0.038	8/0.7	UNIV	1000

REF	Model	Usable length (cm)±5%	O.D. (mm) ±0.10	I.D. (mm) ±0.05	Maximum guidewire O.D. (Inch) ±0.001"	Side hole number/size (mm)±0.2	Curve	Rated burst pressure (psi)
7760090183	6F	90	2.00	1.30	0.038	5/0.7	UNIV	1000
7760090184	6F	90	2.00	1.30	0.038	8/0.7	UNIV	1000
7760110185	6F	110	2.00	1.30	0.038	5/0.7	UNIV	1000
7760110186	6F	110	2.00	1.30	0.038	8/0.7	UNIV	1000
7760080187	6F	80	2.00	1.30	0.038	0	TRG	1000
7760080188	6F	80	2.00	1.30	0.038	1/0.7	TRG	1000
7760100189	6F	100	2.00	1.30	0.038	0	TRG	1000
7760100190	6F	100	2.00	1.30	0.038	1/0.7	TRG	1000
7760110191	6F	110	2.00	1.30	0.038	0	TRG	1000
7760110192	6F	110	2.00	1.30	0.038	1/0.7	TRG	1000
7760080193	6F	80	2.00	1.30	0.038	0	TRG 1	1000
7760080194	6F	80	2.00	1.30	0.038	2/0.7	TRG 1	1000
7760100195	6F	100	2.00	1.30	0.038	0	TRG 1	1000
7760100196	6F	100	2.00	1.30	0.038	2/0.7	TRG 1	1000
7760110197	6F	110	2.00	1.30	0.038	0	TRG 1	1000
7760110198	6F	110	2.00	1.30	0.038	2/0.7	TRG 1	1000
7760080199	6F	80	2.00	1.30	0.038	0	TRG 2	1000
7760080200	6F	80	2.00	1.30	0.038	1/0.7	TRG 2	1000
7760100201	6F	100	2.00	1.30	0.038	0	TRG 2	1000
7760100202	6F	100	2.00	1.30	0.038	1/0.7	TRG 2	1000
7760110203	6F	110	2.00	1.30	0.038	0	TRG 2	1000
7760110204	6F	110	2.00	1.30	0.038	1/0.7	TRG 2	1000